

## FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION 30899

Expires 12/17/2000

30-015-30875-

Operator <u>Gates Petroleum Corp</u>		Lease <u>So. Avalon ASZ St Cam</u>		Well # <u>2</u>	
Location of Well	Unit <u>L</u>	Section <u>14</u>	Township <u>21</u>	Range <u>26</u>	County <u>Eddy</u>
Drilling Contractor <u>AAA</u>	Patterson #78		Type of Equipment <u>Rotary</u>		

## APPROVED CASING PROGRAM

\* Witness 8 5/8 Minimum W.O.C. 18 Hours

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2	13 3/8	48 #		600	550 Circ
12 1/4	* 8 5/8	24 #		2200	1200 Circ
7 7/8	5 1/2	17 #		11,300	400 TOC 8100

Casing Data:

Surface \_\_\_\_\_ joints of \_\_\_\_\_ inch \_\_\_\_\_ # Grade \_\_\_\_\_

(Approved) (Rejected)

Inspected by \_\_\_\_\_ date \_\_\_\_\_

Cementing Program

Size of hole 17 1/2 Size of Casing 13 3/8 Sacks cement required \_\_\_\_\_

Type of Shoe used \_\_\_\_\_ Float collar used \_\_\_\_\_ Btm 3 jts welded \_\_\_\_\_

TD of hole 579' Set \_\_\_\_\_ Feet of 15' Inch \_\_\_\_\_ # Grade \_\_\_\_\_New-used csg. @ 579' with 200 sacks neat cement around shoe+ 200 sacks 579' additives 579' 1/4" 3-100 5# sonitePlug down @ 100 (AM) (PM) Date 2-2-00Cement circulated 0 No. of Sacks 0Cemented by EG Witnessed by \_\_\_\_\_Temp. Survey ran @ 8:30 (AM) (PM) Date 2-2-00 top cement @ 60'

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: ONE 1/2" — 25 x 200