

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-015-30899

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
K-4529

7. Lease Name or Unit Agreement Name
South Avalon ASZ State Com

8. Well No.
2

9. Pool name or Wildcat
Burton Flat Morrow

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3162' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter L : 1650 Feet From The South Line and 660 Feet From The West Line
Section 14 Township 21S Range 26E NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: Spud, conductor, surface casing & cement <input checked="" type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole with rat hole at 9:00 AM 1-26-2000. Set 40' of 20" conductor pipe. Cemented to surface. NOTE: Notified Mike w/OCD-Artesia of spud. Resumed drilling a 17-1/2" hole with rotary tools at 12:15 AM 2-1-2000. NOTE: Notified Mike w/OCD-Artesia of resuming drilling.

TD 579'. Reached TD at 9:30 PM 2-1-2000. Ran 13 joints of 13-3/8" 48# H-40 (583.54') of casing set at 579'. 1-Texas Pattern notched guide shoe set at 578'. Insert float set at 533'. Cemented with 200 sacks "H" cement, 10% A-10B, 1% CaCl₂, 1/4#/sack celloflake and 10#/sack gilsonite (yield 1.52, weight 14.6) and 295 sacks Poz C (65-35), 5#/sack salt, 1/4#/sack celloflake and 5#/sack gilsonite (yield 2.04, weight 12.5). Tailed in with 200 sacks "C" and 2% CaCl₂ (yield 1.34, weight 14.8). PD 3:15 AM 2-2-2000. Bumped plug to 200 psi, OK. Cement did not circulate. WOC 6 hours and ran Temperature Survey and found top of cement at 60'. Ran 1". Tagged cement at 57'. Spotted 35 sacks "C" with 4% CaCl₂. PD 10:15 AM 2-2-2000. WOC 1-1/2 hour. Ran 1". Tagged cement at 55-1/2'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

CONTINUED ON NEXT PAGE:

SIGNATURE Rusty Klein TITLE Operations Technician DATE June 26, 2000

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Jim W. Green B6A

District Supervisor

JUL 03 2000