

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-015-30899

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
K-4529

7. Lease Name or Unit Agreement Name
South Avalon ASZ State Com

8. Well No.
2

9. Pool name or Wildcat
Burton Flat Morrow

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3162' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter L : 1650 Feet From The South Line and 660 Feet From The West Line
Section 14 Township 21S Range 26E NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Production casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 11224'. Reached TD at 6:30 PM 3-24-2000. Ran 267 joints of 4-1/2" 11.6# casing as follows: 28 joints of 4-1/2" 11.6# S/P110 8rd (1608.85'); 1 joint of 4-1/2" 11.6# S/P 110 8rd marker joint (21.36') and 228 joints of 4-1/2" 11.6# S/P 110 (9596.13') (Total 11226.34') of casing set at 11224'. Float shoe set at 11224'. Float collar set at 11178'. Pumped 150 bbls of mud with 150 scf/bbl N2 ahead of 1450 sacks 65-35-6, 3#/sack salt, 5#/sack gilsonite and 1/4#/sack celloflake (yield 2.04, weight 12.4). Tailed in with 700 sacks Super C Modified, 7/10% FL52, 7/10% FL25, 5#/sack gilsonite and 2% KCL (yield 1.60, weight 13.2). PD 8:45 AM 3-27-2000. Bumped plug to 3050 psi for 5 minutes, OK. WOC. Released rig at 4:00 PM 3-27-2000.

Waiting on completion unit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Rusty Klein

TITLE

Operations Technician

DATE June 26, 2000

TELEPHONE NO. 505/748-1471

TYPE OR PRINT NAME

Rusty Klein

(This space for State Use)

ORIGINAL SIGNED BY TIA W. GUM
DISTRICT II SUPERVISOR BOK

APPROVED BY

TITLE

DATE

JUL 03 2000

CONDITIONS OF APPROVAL, IF ANY: