

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

30-015-30983

Operator <u>Nadel and Gussman Permian</u>		Lease <u>Sammy State</u>		Well # <u>1</u>	
Location of Well	Unit <u>E</u>	Section <u>15</u>	Township <u>21</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor <u>Patterson</u>	# <u>1</u>		Type of Equipment <u>Rotary</u>		

3/1/00 Per Dale Miller will spud today

APPROVED CASING PROGRAM

* Witness 13 3/8 + 8 5/8

Size of Hole	Size of Casing	Weight per Ft	New or Used	Depth	Sacks Cement
<u>24</u>	<u>20</u>	<u>48 #</u>		<u>40'</u>	<u>10 Surf - Circ.</u>
<u>17 1/2</u>	* <u>13 3/8</u>	<u>42</u>	<u>3-13-00</u>	<u>400'</u>	<u>900 Circ Surf</u>
<u>12 1/4</u>	* <u>8 5/8</u>	<u>36</u>		<u>1900'</u>	<u>1000 Circ Surf</u>
<u>7 7/8</u>	<u>5 1/2</u>	<u>17 + 20</u>		<u>10,800'</u>	<u>1000 Tie Back to 8 5/8</u>

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____

(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole 17 1/2 Size of Casing 13 3/8 Sacks cement required _____

Type of Shoe used _____ Float collar used _____ Btm 3 jts welded _____

TD of hole 405 Set 410 Feet of 13 3/8 Inch 48 # Grade J-55

New-used csg. @ _____ with 400 sacks neat cement around shoe
+ 245 sack 35.65 additives 6% Cact GEL 2% Cact

Plug down @ 7:45 (AM) (PM) Date 3-13-00 3-13-00

Cement circulated 395x No. of Sacks _____

Cemented by B.J. Witnessed by _____

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____