Fora 3160-5 (August 1999)

N.M. Oll Cons. Livipion

811 S. 1st Street

FORM APPROVED OMB No. 1004-0135 Expires November 30, 2000

DEPARTMENT OF THE INTERIOR Artesia, NM 88210-2834se Serial No.

UNITED STATES

arthent or agency of the United

SUNDRY NOTICES AND REPORTS ON WI Do not use this form for proposals to drill or to re abandoned well. Use Form 3160-3 (APD) for such pr	enter an 6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE - Other instructions on r	7. If Unit or CA/Agreement, Name and/or No.
1. Type of Well Oil Well Gas Well Other	7. If Unit or CA/Agreement, Name and/or No. 8. Well Name and No.
2. Name of Operator Yates Petroleum Corporation Mule Deer ATU Federal Com #1 9. API Well No.	
3a. Address 105 S. 4th St Artesia, NM 88210 505-7	o (include area code) 30-015-30985 10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1559' FSL & 1438' FWL of Section 11-T21S-R21E (Unit K, NESW) Eddy Co., NM	
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	
TYPE OF SUBMISSION TYPE OF ACTION	
Acidize Deepen Acidize Deepen Alter Casing Fracture To Casing Repair New Const	ruction Recomplete X Other Intermediate
☐ Change Plans ☐ Plug and A ☐ Final Abandonment Notice ☐ Convert to Injection ☐ Plug Back	bandon
following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 31604 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) TD 2023'. Reached TD at 2:15 AM 5-2-2000. Ran 45 joints of 9-5/8" 36# J-55 (2028.97') of casing set at 2023'. Regular guide shoe set at 2022'. Float collar set at 1976'. Cemented with 200 sacks "H", 10% A-10B, 1% CaCl2, 1/4#/sack celloflake and 10#/sack gilsonite (yield 1.52, weight 14.6) and 800 sacks Poz C (65-35), 5#/sack salt, 1/4#/sack celloflake and 10#/sack gilsonite (yield 1.90, weight 12.8). Tailed in with 200 sacks "C" and 2% CaCl2 (yield 1.32, weight 14.8). PD 12:45 PM 5-2-2000. Bumped plug to 981 psi, 0K. Cement did not circulate. WOC 6 hours. Ran Temperature Survey and found top of cement at 700'. Ran 1". Tagged cement at 602'. Spotted 50 sacks "C" and 4% CaCl2. PD 11:30 PM 5-2-2000. WOC 2 hours. Ran 1". Tagged cement at 491'. Spotted 75 sacks "C" and 4% CaCl2. PD 1:30 AM 5-3-2000. WOC 2 hours. Ran 1". Tagged cement at 478'. Spotted 100 sacks "C" and 4% CaCl2. PD 4:00 AM 5-3-2000. WOC 2 hours. Ran 1". Tagged cement at 478'. Spotted 100 sacks "C" and 4% CaCl2. PD 6:15 AM 5-3-2000. WOC 1-3/4 hour. Ran 1". Tagged cement at 478'. Spotted 75 sacks "C" and 4% CaCl2. PD 6:15 AM 5-3-2000. WOC 1-3/4 hour. Ran 1". Tagged cement at 478'. Spotted 100 sacks "C" and 4% CaCl2. PD 6:15 AM 5-3-2000. WOC 1-3/4 hour. Ran 1". Tagged cement at 478'. Spotted 100 sacks "C" and 4% CaCl2. PD 6:15 AM 5-3-2000. WOC 1-3/4 hour. Ran 1". Tagged cement at 478'. Spotted 100 sacks "C" and 4% CaCl2. PD 6:15 AM 5-3-2000. WOC 1-3/4 hour. Ran 1". Tagged cement at 478'. Spotted 100 sacks "C" and 4% CaCl2. PD 6:15 AM 5-3-2000. WOC 1-3/4 hour. Ran 1". Tagged cement at 478'. Spotted 100 sacks "C" and 4% CaCl2. PD 6:15 AM 5-3-2000. WOC 1-3/4 hour. Ran 1". Tag	
Rusty Klein	Title Operations Technician
Signature Kusley VIII	Date August 31, 2000
THIS SPACE FOR FEDERAL OR STATE OFFICE USE	
Approved by Conditions of approval, if any, are attached. Approval of this notice does not warr certify that the applicant holds legal or equitable title to those rights in the subject which would entitle the applicant to conduct operations thereon.	Title ACCEPTED FOR REGORD ant or lease Office OCT 0.5 2000

and willfully to make to any de

RIM

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

YATES PETROLEUM CORPORATION Mule Deer ATU Federal Com #1 Section 11-T21S-R21E Eddy County, New Mexico

SUNDRY NOTICE CONTINUED:

C and 5% CaCl2. PD 10:45 AM 5-3-2000. WOC 1-1/4 hour. Ran 1". Tagged cement at 422'. Spotted 50 sacks Class C and 5% CaCl2. PD 12:30 PM 5-3-2000. WOC 1-1/2 hour. Ran 1". Tagged cement at 366'. Spotted 75 sacks "C" and 5% CaCl2. PD 2:00 PM 5-3-2000. WOC 1-1/4 hour. Ran 1". Tagged cement at 31'. Spotted 50 sacks "C" and 2% CaCl2. PD 3:30 PM 5-3-2000. Circulated 10 sacks. WOC. Nippled up and tested to 3000 psi for 15 minutes. Drilled out at 3:15 AM 5-5-2000. WOC 62 hours and 30 minutes. Reduced hole to 8-3/4". Resumed drilling. NOTE: Notified Don Early w/BLM-Carlsbad of casing job - Don Early witnessed.

Rusty Klein

Operations Technician

August 31, 2000