

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-015-31003
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	V-3576
7. Lease Name or Unit Agreement Name	Aviette ALK State Com
8. Well No.	2
9. Pool name or Wildcat	Burton Flat Morrow
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	3248' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT
(FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:	OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER
2. Name of Operator	YATES PETROLEUM CORPORATION
3. Address of Operator	105 South 4th St., Artesia, NM 88210

4. Well Location	Unit Letter 0 : 860 Feet From The South Line and 1980 Feet From The East Line
Section 17	Township 21S Range 27E NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Spud, conductor, resume drilling, surface casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole with rat hole machine at 3:30 PM 5-15-2000. Drilled to 40'. Set 40' of 20" conductor pipe. Cemented to surface. NOTE: Notified Mike Stubblefield w/OCD-Artesia of spud. Resumed drilling a 17-1/2" hole with rotary tools at 9:00 AM 5-17-2000.

TD 594'. Reached TD at 8:00 PM 5-17-2000. Ran 13 joints of 13-3/8" 48# H-40 (598.81') of casing set at 594'. 1-Texas Pattern notched guide shoe set at 594'. Insert float set at 547'. Cemented with 100 sacks "H", 10% A-10B, 10#/sack gilsonite, 295 sacks 65-35-6, 5#/sack salt, 1/4#/sack celloflake and 5#/sack gilsonite (yield 2.04, weight 12.5). Tailed in with 200 sacks "C" and 2% CaCl2 (yield 1.34, weight 14.8). PD 1:15 AM 5-18-2000. Bumped plug to 720 psi, OK. Circulated 120 sacks. WOC. Installed rotating head. Drilled out at 8:30 PM 5-18-2000. WOC 19 hours and 30 minutes. Reduced hole to 12-1/4". Resumed drilling. NOTE: Notified Mike Stubblefield w/OCD-Artesia of resume drilling and cementing.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE Sept. 20, 2000

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-147

(This space for State Use)

ORIGINAL AGED BY THE W. GUM
DISTRICT II SUPERVISOR

NOV 03 2000

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: