

Company	BONNEVILLE FUELS					Target Tvd #1	Target Tvd #4		N/S(+/-)			
Well	AVALON 1 FEDERAL #2					Target Deg #1	Target Deg #4		E/W(+/-)			
Field	FOSTER DRAW					Target Tvd #2	Planned Direction		165.90	N-S SURF FT.		
Rig	UTI RIG NO. 154					Target Deg #2	Tgt. Coord.		E-W SURF FT.			
Driller	SPERRY					Target Tvd #3	Page		2	Of		
						Target Deg #3	Magnetic Declination					
Date	No.	DEPTH	INC.	AZM	C.L.	T.V.D.	V.S.	N(+)/S(-)	E(+)/W(-)	DLS	BUILD	WALK
	41	3180	45.90	158.80	32	2934.28	654.44	-633.83	162.99	1.38	0.31	-1.875
	42	3212	45.20	158.00	32	2956.69	677.08	-655.07	171.39	2.82	-2.19	-2.50
	43	3244	43.80	157.80	32	2979.51	699.29	-675.85	179.83	4.40	-4.38	-0.62
	44	3275	41.60	157.20	31	3002.29	720.09	-695.27	187.87	7.22	-7.10	-1.94
	45	3307	39.40	157.50	32	3026.62	740.64	-714.45	195.88	6.90	-6.88	0.94
	46	3339	38.80	158.70	32	3051.46	760.63	-733.17	203.41	3.02	-1.88	3.75
	47	3371	37.80	160.80	32	3076.57	780.35	-751.77	210.27	5.13	-3.13	6.56
	48	3402	35.00	159.10	31	3101.52	798.64	-769.05	216.57	9.60	-9.03	-5.48
	49	3434	32.50	159.70	32	3128.13	816.31	-785.69	222.83	7.88	-7.81	1.87
	50	3466	32.60	159.00	32	3155.10	833.41	-801.80	228.90	1.22	0.31	-2.19
	51	3498	32.10	159.40	32	3182.13	850.42	-817.81	234.98	1.70	-1.56	1.25
	52	3529	32.40	157.90	31	3208.35	866.82	-833.22	241.00	2.76	0.97	-4.84
	53	3561	31.80	157.60	32	3235.46	883.66	-848.95	247.44	1.94	-1.87	-0.94
	54	3593	31.40	157.70	32	3262.71	900.25	-864.46	253.82	1.26	-1.25	0.31
	55	3624	30.30	157.60	31	3289.33	915.98	-879.16	259.86	3.55	-3.55	-0.32
	56	3656	29.80	159.80	32	3317.03	931.88	-894.09	265.68	3.78	-1.56	6.88
	57	3688	30.00	159.60	32	3344.77	947.74	-909.05	271.22	0.70	0.62	-0.63
	58	3719	30.10	159.80	31	3371.60	963.17	-923.61	276.60	0.46	0.32	0.65
	59	3751	29.60	160.80	32	3399.36	979.02	-938.61	281.97	2.20	-1.56	3.13
	60	3783	30.00	161.90	32	3427.12	994.87	-953.67	287.06	2.12	1.25	3.44
	61	3815	30.10	161.00	32	3454.82	1010.85	-968.86	292.15	1.44	0.31	-2.81
	62	3846	29.70	162.00	31	3481.70	1026.25	-983.52	297.06	2.06	-1.29	3.23
	63	3878	29.30	164.30	32	3509.55	1041.99	-998.60	301.63	3.75	-1.25	7.19
	64	3909	28.90	166.10	31	3536.64	1057.06	-1013.17	305.48	3.10	-1.29	5.81
	65	3941	27.80	165.80	32	3564.80	1072.26	-1027.91	309.17	3.47	-3.44	-0.94
	66	3973	27.40	167.90	32	3593.16	1087.08	-1042.35	312.54	3.29	-1.25	6.56
	67	4003	27.40	167.00	30	3619.79	1100.88	-1055.82	315.54	1.38		-3.00
	68	4035	27.40	167.10	32	3648.20	1115.60	-1070.17	318.84	0.14		0.31
	69	4067	27.30	166.10	32	3676.62	1130.30	-1084.47	322.25	1.47	-0.31	-3.13
	70	4099	27.20	166.90	32	3705.07	1144.95	-1098.72	325.67	1.19	-0.31	2.50
	71	4131	27.50	166.10	32	3733.50	1159.66	-1113.02	329.10	1.48	0.94	-2.50
	72	4162	27.30	165.20	31	3761.02	1173.92	-1126.84	332.64	1.48	-0.65	-2.90
	73	4194	27.50	166.00	32	3789.43	1188.65	-1141.10	336.30	1.31	0.62	2.50
	74	4226	27.40	165.60	32	3817.83	1203.40	-1155.40	339.92	0.66	-0.31	-1.25
	75	4276	27.40	165.60	50	3862.22	1226.41	-1177.69	345.64			
	76											
	77											
	78											
	79											
	80											
	81											
	82											

Bottom Hole : 1508' FSL & 1653' FEL
 Top Perfor : 1685' FSL & 1647' FEL