				_	0 51	
			Oil Cons		• [/	
orm 3160-5	UN	TED STATES	N.M. DIV-D	ist. 2	FORM APPROVED	
une 1990)		T OF THE INTERIOR	1301 W. Grand	Avenue	nt Bureau No. 1004-0135 pires: March 31, 1993	
	BUREAU OF	LAND MANAGEMENT	Artesia, NM	88210 Lese D	NM 18964	
	SUNDRY NOTICES	AND REPORTS ON V	NELLS		Allottee or Tribe Name	
Do not use this fo	orm for proposals to di ise "APPLICATION FO	ill or to deepen or reent R PERMIT—" for such	try to a different reser proposals	voir.		
	SUBMI	IN TRIPLICATE		7. If Unit c	r CA, Agreement Designation	
1. Type of Well Oil Gas Well Well	Other			8. Well Nan	e and No.	
2. Name of Operator					El Paso Federal No. 10	
Fasken Oil and Ranch, Ltd.				9. API Well	No. 30-015-31147	
3. Address and Telephone No. 303 W. Wall, Suite 1800, Midland, TX 79701 (915) 687-1777					d Pool, or Exploratory Area	
	e, Sec., T., R., M., or Survey E				Undesignated	
				11. County	or Parish, State	
2105' FSL, 1350' FI	EL, Section 2, T21S, R26	E		l l	Eddy, NM	
2. CHECK	APPROPRIATE BOX	s) TO INDICATE NAT	URE OF NOTICE, R	EPORT, OR O	THER DATA	
TYPE OF	TYPE OF SUBMISSION TYPE OF					
Notice of	of latent	Abandon	ment		e of Plans	
_		Recompl	etion		Construction	
Subsequ	ent Report	Plugging			Routine Fracturing	
		Casing F	Kepair			
			Casing	Conv	ention to Injection	
Final A	bandonment Notice	Altering	Casing		ersion to Injection ose Water	
3. Describe Proposed or Co	mpleted Operations (Clearly state	U pertinent details, and give pertinent	nt dates, including estimated date of	(Note: Rep (Note: Rep Completion	one Water or results of multiple completion on Well or Recompletion Report and Log form.) work. If well is directionally drillo	
 Describe Proposed or Cogive subsurface local 4/12/01 Moved in a plug with dump bai CCL from 3500' - 2 2200 gals. 7 1/2% bpm @ 1250 psi. 1 12/20 Super LC rest 	mpleted Operations (Clearly state ations and measured and true vert and rigged up on well. PC ler. Circulated well with 280'. Perforated at 2407 NEFE HCL containing 6 Frac'd perfs w/ 20,000 ga sin coated sand. Flowed	Other	nt dates. including estimated date of s pertinent to this work.)* Ran 5 1/2" CIBP and set sted casing to 2200 psi. 56', 2476' - 78', 80' (31 h rrotrol 271, 2 gpt NE 940 ked CMHPG gel plus 25 0 MCFG, 105 BW. Wel	Disp (Note: Rep Completion of starting any proposed at 3650'. Placed Spotted 300 gal oles). Acidized r 1, 1 gpt Cl-27, 1 g ,200# 12/20 Brov I shut in and drop	ose Water or results of multiple completion on Well or Recompletion Report and Log form.) work. If well is directionally drille 35' of Class C cement is 7 1/2% acid. Ran GR- new perforations with pt Claymaster 5C at 4.5 or sand plus 25,300# oped from report.	
 Describe Proposed or Cogive subsurface local 4/12/01 Moved in a plug with dump bai CCL from 3500' - 2 2200 gals. 7 1/2% bpm @ 1250 psi. 1 12/20 Super LC rest 	mpleted Operations (Clearly state ations and measured and true vert and rigged up on well. PC ler. Circulated well with 280'. Perforated at 2407 NEFE HCL containing 6 Frac'd perfs w/ 20,000 ga sin coated sand. Flowed	Dother Ill pertinent details, and give pertiner cal depths for all markers and zone OH with rods and tubing. R '5 bbls 2% KCL water. Te ', 09', 10', 13', 16', 2433' - ! gpt Ferrotrol 270, 2 gpt Fer Is Medallion 3000 crosslind well on production. 0 BO,	nt dates. including estimated date of s pertinent to this work.)* Ran 5 1/2" CIBP and set sted casing to 2200 psi. 56', 2476' - 78', 80' (31 h rrotrol 271, 2 gpt NE 940 ked CMHPG gel plus 25 0 MCFG, 105 BW. Wel	Disp (Note: Rep Completion of starting any proposed at 3650'. Placed Spotted 300 gal oles). Acidized r 1, 1 gpt Cl-27, 1 g ,200# 12/20 Brov I shut in and drop	be Water or results of multiple completion on Well or Recompletion Report and Log form.) work. If well is directionally drille 35' of Class C cement is 7 1/2% acid. Ran GR- new perforations with pt Claymaster 5C at 4.5 or sand plus 25,300#	
 Describe Proposed or Cogive subsurface local 4/12/01 Moved in a plug with dump bai CCL from 3500' - 2 2200 gals. 7 1/2% bpm @ 1250 psi. 1 12/20 Super LC rest 	mpleted Operations (Clearly state ations and measured and true vert and rigged up on well. PC ler. Circulated well with 280'. Perforated at 2407 NEFE HCL containing 6 Frac'd perfs w/ 20,000 ga sin coated sand. Flowed	Dother Ill pertinent details, and give pertiner cal depths for all markers and zone OH with rods and tubing. R '5 bbls 2% KCL water. Te ', 09', 10', 13', 16', 2433' - ! gpt Ferrotrol 270, 2 gpt Fer Is Medallion 3000 crosslind well on production. 0 BO,	nt dates. including estimated date of s pertinent to this work.)* Ran 5 1/2" CIBP and set sted casing to 2200 psi. 56', 2476' - 78', 80' (31 h rrotrol 271, 2 gpt NE 940 ked CMHPG gel plus 25 0 MCFG, 105 BW. Wel	Disp (Note: Rep Completion of starting any proposed at 3650'. Placed Spotted 300 gal oles). Acidized r 1, 1 gpt Cl-27, 1 g ,200# 12/20 Brov I shut in and drop	ose Water or results of multiple completion on Well or Recompletion Report and Log form.) work. If well is directionally drille 35' of Class C cement is 7 1/2% acid. Ran GR- new perforations with pt Claymaster 5C at 4.5 or sand plus 25,300# oped from report.	
 Describe Proposed or Cogive subsurface loc 4/12/01 Moved in a plug with dump bai CCL from 3500' - 2 2200 gals. 7 1/2% bpm @ 1250 psi. 1 12/20 Super LC res 	mpleted Operations (Clearly state ations and measured and true vert and rigged up on well. PC ler. Circulated well with 280'. Perforated at 2407 NEFE HCL containing 6 Frac'd perfs w/ 20,000 ga sin coated sand. Flowed	Dother Ill pertinent details, and give pertiner cal depths for all markers and zone OH with rods and tubing. R '5 bbls 2% KCL water. Te ', 09', 10', 13', 16', 2433' - ! gpt Ferrotrol 270, 2 gpt Fer Is Medallion 3000 crosslind well on production. 0 BO,	nt dates. including estimated date of spertinent to this work.)* Ran 5 1/2" CIBP and set sted casing to 2200 psi. 56', 2476' - 78', 80' (31 h rrotrol 271, 2 gpt NE 940 ked CMHPG gel plus 25 0 MCFG, 105 BW. Wel ial of the well.	Disp (Note: Rep Completion of starting any proposed at 3650'. Placed Spotted 300 gal oles). Acidized r 1, 1 gpt Cl-27, 1 g ,200# 12/20 Brov I shut in and drop	one Water or results of multiple completion on Well or Recompletion Report and Log form.) work. If well is directionally drille 35' of Class C cement is 7 1/2% acid. Ran GR- new perforations with pt Claymaster 5C at 4.5 or sand plus 25,300# oped from report.	
 Describe Proposed or Cogive subsurface local 4/12/01 Moved in a plug with dump bai CCL from 3500' - 2 2200 gals. 7 1/2% bpm @ 1250 psi. 1 12/20 Super LC rest 	mpleted Operations (Clearly state ations and measured and true vert and rigged up on well. PC ler. Circulated well with 280'. Perforated at 2407 NEFE HCL containing 6 Frac'd perfs w/ 20,000 ga sin coated sand. Flowed	Dother Ill pertinent details, and give pertiner cal depths for all markers and zone OH with rods and tubing. R '5 bbls 2% KCL water. Te ', 09', 10', 13', 16', 2433' - ! gpt Ferrotrol 270, 2 gpt Fer Is Medallion 3000 crosslind well on production. 0 BO,	nt dates. including estimated date of spertinent to this work.)* Ran 5 1/2" CIBP and set sted casing to 2200 psi. 56', 2476' - 78', 80' (31 h rrotrol 271, 2 gpt NE 940 ked CMHPG gel plus 25 0 MCFG, 105 BW. Wel ial of the well.	Disp (Note: Rep Completion of starting any proposed at 3650'. Placed Spotted 300 gal oles). Acidized r 1, 1 gpt Cl-27, 1 g ,200# 12/20 Brov I shut in and drop	be Water re results of multiple completion on Well or Recompletion Report and Log form.) work. If well is directionally drille 35' of Class C cement is 7 1/2% acid. Ran GR- new perforations with pt Claymaster 5C at 4.5 or sand plus 25,300# oped from report.	
 Describe Proposed or Cogive subsurface loc 4/12/01 Moved in a plug with dump bai CCL from 3500' - 2 2200 gals. 7 1/2% bpm @ 1250 psi. 1 12/20 Super LC res 	mpleted Operations (Clearly state ations and measured and true vert and rigged up on well. PC ler. Circulated well with 280'. Perforated at 2407 NEFE HCL containing 6 Frac'd perfs w/ 20,000 ga sin coated sand. Flowed	Dother Ill pertinent details, and give pertiner cal depths for all markers and zone OH with rods and tubing. R '5 bbls 2% KCL water. Te ', 09', 10', 13', 16', 2433' - ! gpt Ferrotrol 270, 2 gpt Fer Is Medallion 3000 crosslind well on production. 0 BO,	nt dates. including estimated date of spertinent to this work.)* Ran 5 1/2" CIBP and set sted casing to 2200 psi. 56', 2476' - 78', 80' (31 h rrotrol 271, 2 gpt NE 940 ked CMHPG gel plus 25 0 MCFG, 105 BW. Wel ial of the well.	Disp (Note: Rep Completion of starting any proposed at 3650'. Placed Spotted 300 gal oles). Acidized r 1, 1 gpt Cl-27, 1 g ,200# 12/20 Brov I shut in and drop	one Water or results of multiple completion on Well or Recompletion Report and Log form.) work. If well is directionally drille 35' of Class C cement is 7 1/2% acid. Ran GR- new perforations with pt Claymaster 5C at 4.5 or sand plus 25,300# oped from report.	
 Describe Proposed or Cogive subsurface local 4/12/01 Moved in a plug with dump bai CCL from 3500' - 2 2200 gals. 7 1/2% bpm @ 1250 psi. 1 12/20 Super LC rest 	mpleted Operations (Clearly state ations and measured and true vert and rigged up on well. PC ler. Circulated well with 280'. Perforated at 2407 NEFE HCL containing 6 Frac'd perfs w/ 20,000 ga sin coated sand. Flowed	Dother Ill pertinent details, and give pertiner cal depths for all markers and zone OH with rods and tubing. R '5 bbls 2% KCL water. Te ', 09', 10', 13', 16', 2433' - ! gpt Ferrotrol 270, 2 gpt Fer Is Medallion 3000 crosslind well on production. 0 BO,	nt dates. including estimated date of spertinent to this work.)* Ran 5 1/2" CIBP and set sted casing to 2200 psi. 56', 2476' - 78', 80' (31 h rrotrol 271, 2 gpt NE 940 ked CMHPG gel plus 25 0 MCFG, 105 BW. Wel ial of the well.	Disp (Note: Rep Completion of starting any proposed at 3650'. Placed Spotted 300 gal oles). Acidized r 1, 1 gpt Cl-27, 1 g ,200# 12/20 Brov I shut in and drop	ose Water or results of multiple completion on Well or Recompletion Report and Log form.) work. If well is directionally drille 35' of Class C cement is 7 1/2% acid. Ran GR- new perforations with pt Claymaster 5C at 4.5 or sand plus 25,300# oped from report.	
 Describe Proposed or Cogive subsurface local 4/12/01 Moved in a plug with dump bai CCL from 3500' - 2 2200 gals. 7 1/2% bpm @ 1250 psi. 1 12/20 Super LC rest 	mpleted Operations (Clearly state ations and measured and true vert and rigged up on well. PC ler. Circulated well with 280'. Perforated at 2407 NEFE HCL containing 6 Frac'd perfs w/ 20,000 ga sin coated sand. Flowed	Dother Ill pertinent details, and give pertiner cal depths for all markers and zone OH with rods and tubing. R '5 bbls 2% KCL water. Te ', 09', 10', 13', 16', 2433' - ! gpt Ferrotrol 270, 2 gpt Fer Is Medallion 3000 crosslind well on production. 0 BO,	nt dates. including estimated date of spertinent to this work.)* Ran 5 1/2" CIBP and set sted casing to 2200 psi. 56', 2476' - 78', 80' (31 h rrotrol 271, 2 gpt NE 940 ked CMHPG gel plus 25 0 MCFG, 105 BW. Wel ial of the well.	Disp (Note: Rep Completion of starting any proposed at 3650'. Placed Spotted 300 gal oles). Acidized r 1, 1 gpt Cl-27, 1 g ,200# 12/20 Brov I shut in and drop	be Water re results of multiple completion on Well or Recompletion Report and Log (orm.) work. If well is directionally drilled 35' of Class C cement is 7 1/2% acid. Ran GR- new perforations with pt Claymaster 5C at 4.5 or sand plus 25,300# oped from report.	
 Describe Proposed or Co give subsurface local 4/12/01 Moved in a plug with dump bail CCL from 3500' - 2 2200 gals. 7 1/2% bpm @ 1250 psi. 1 12/20 Super LC res Temporary abando 	inpleted Operations (Clearly state ations and measured and true vert ind rigged up on well. PC ler. Circulated well with 7 280'. Perforated at 2407 NEFE HCL containing 6 Frac'd perfs w/ 20,000 ga sin coated sand. Flowed onment applied for pendir	Dother Ill pertinent details, and give pertiner cal depths for all markers and zone OH with rods and tubing. R '5 bbls 2% KCL water. Te ', 09', 10', 13', 16', 2433' - ! gpt Ferrotrol 270, 2 gpt Fer Is Medallion 3000 crosslind well on production. 0 BO,	nt dates. including estimated date of spertinent to this work.)* Ran 5 1/2" CIBP and set sted casing to 2200 psi. 56', 2476' - 78', 80' (31 h rrotrol 271, 2 gpt NE 940 ked CMHPG gel plus 25 0 MCFG, 105 BW. Wel ial of the well.	Disp (Note: Rep Completion of starting any proposed at 3650'. Placed Spotted 300 gal oles). Acidized r 1, 1 gpt Cl-27, 1 g ,200# 12/20 Brov I shut in and drop	ose Water or results of multiple completion on Well or Recompletion Report and Log form.) work. If well is directionally drille 35' of Class C cement is 7 1/2% acid. Ran GR- new perforations with pt Claymaster 5C at 4.5 or sand plus 25,300# oped from report.	
 Describe Proposed or Co give subsurface loca 4/12/01 Moved in a plug with dump bai CCL from 3500' - 2 2200 gals. 7 1/2% bpm @ 1250 psi. 1 12/20 Super LC res Temporary abando 14. I hereby certify plus, the With the subscript of the subs	mpleted Operations (Clearly state ations and measured and true vert and rigged up on well. PC ler. Circulated well with 280'. Perforated at 2407 NEFE HCL containing 6 Frac'd perfs w/ 20,000 ga sin coated sand. Flowed	Deter Il pertinent details, and give pertinent cal depths for all markers and zone)H with rods and tubing. R '5 bbls 2% KCL water. Te ', 09', 10', 13', 16', 2433' - 1 gpt Ferrotrol 270, 2 gpt Fer Is Medallion 3000 crosslind well on production. 0 BO, g further economic potenti Begulate	nt dates. including estimated date of spertinent to this work.)* Ran 5 1/2" CIBP and set sted casing to 2200 psi. 56', 2476' - 78', 80' (31 h rrotrol 271, 2 gpt NE 940 ked CMHPG gel plus 25 0 MCFG, 105 BW. Wel ial of the well.	Disp (Note: Rep Completion of starting any proposed at 3650'. Placed Spotted 300 gal ioles). Acidized r 1, 1 gpt Cl-27, 1 g ,200# 12/20 Brow I shut in and drop	bee Water or results of multiple completion on Well or Recompletion Report and Log form.) work. If well is directionally drille 35' of Class C cement is 7 1/2% acid. Ran GR- new perforations with pt Claymaster 5C at 4.5 or sand plus 25,300# oped from report. 11/20/2001	
 Describe Proposed or Co give subsurface loca 4/12/01 Moved in a plug with dump bai CCL from 3500' - 2 2200 gals. 7 1/2% bpm @ 1250 psi. 1 12/20 Super LC res Temporary abando Temporary abando 	Ind rigged up on well. PC ler. Circulated well with 7 280'. Perforated at 2407 NEFE HCL containing 6 Frac'd perfs w/ 20,000 ga sin coated sand. Flowed onment applied for pendir	Deter Il pertinent details, and give pertinent cal depths for all markers and zone H with rods and tubing. F '5 bbls 2% KCL water. Te ', 09', 10', 13', 16', 2433' - 1 "gpt Ferrotrol 270, 2 gpt Fer Is Medallion 3000 crosslini well on production. 0 BO, g further economic potenti	nt dates. including estimated date of a pertinent to this work.)* Ran 5 1/2" CIBP and set sted casing to 2200 psi. 56', 2476' - 78', 80' (31 h rrotrol 271, 2 gpt NE 940 ked CMHPG gel plus 25 0 MCFG, 105 BW. Wel ial of the well.	Disp (Note: Rep Completion of starting any proposed at 3650'. Placed Spotted 300 gal oles). Acidized r 1, 1 gpt Cl-27, 1 g ,200# 12/20 Brov I shut in and drop	bee Water or results of multiple completion on Well or Recompletion Report and Log form.) work. If well is directionally drille 35' of Class C cement is 7 1/2% acid. Ran GR- new perforations with pt Claymaster 5C at 4.5 or sand plus 25,300# oped from report. 11/20/2001	
 13. Describe Proposed or Cogive subsurface loci 4/12/01 Moved in a plug with dump bai CCL from 3500' - 2 2200 gals. 7 1/2% bpm @ 1250 psi. 1 12/20 Super LC reater Temporary abando 14. I hereby certify that the signed	Ind rigged up on well. PC ler. Circulated well with 7 280'. Perforated at 2407 NEFE HCL containing 6 Frac'd perfs w/ 20,000 ga sin coated sand. Flowed onment applied for pendir	U pertinent details, and give pertiner cal depths for all markers and zone OH with rods and tubing. F 75 bbls 2% KCL water. Te 7, 09', 10', 13', 16', 2433' - 1 9pt Ferrotrol 270, 2 gpt Fer Is Medallion 3000 crosslini well on production. 0 BO, g further economic potenti	nt dates. including estimated date of a pertinent to this work.)* Ran 5 1/2" CIBP and set sted casing to 2200 psi. 56', 2476' - 78', 80' (31 h rrotrol 271, 2 gpt NE 940 ked CMHPG gel plus 25 0 MCFG, 105 BW. Wel ial of the well.	Disp (Note: Rep Completion of starting any proposed at 3650'. Placed Spotted 300 gal ioles). Acidized r 1, 1 gpt Cl-27, 1 g ,200# 12/20 Brow I shut in and drop	by Water or results of multiple completion on Well or Recompletion Report and Log form.) work. If well is directionally drille 35' of Class C cement is 7 1/2% acid. Ran GR- new perforations with pt Claymaster 5C at 4.5 or sand plus 25,300# oped from report. 11/20/2001	
 Describe Proposed or Co give subsurface loca 4/12/01 Moved in a plug with dump bai CCL from 3500' - 2 2200 gals. 7 1/2% bpm @ 1250 psi. 1 12/20 Super LC res Temporary abando Temporary abando 	Indrigged up on well. PC ler. Circulated well with 280'. Perforated at 2407 NEFE HCL containing 6 Frac'd perfs w/ 20,000 ga sin coated sand. Flowed onment applied for pendir	Deter Il pertinent details, and give pertinent cal depths for all markers and zone)H with rods and tubing. R '5 bbls 2% KCL water. Te ', 09', 10', 13', 16', 2433' - 1 gpt Ferrotrol 270, 2 gpt Fer Is Medallion 3000 crosslind well on production. 0 BO, g further economic potenti Begulate	nt dates. including estimated date of a pertinent to this work.)* Ran 5 1/2" CIBP and set sted casing to 2200 psi. 56', 2476' - 78', 80' (31 h rrotrol 271, 2 gpt NE 940 ked CMHPG gel plus 25 0 MCFG, 105 BW. Wel ial of the well.	Completion (Note: Rep Completion of starting any proposed at 3650'. Placed Spotted 300 gal ioles). Acidized r 1, 1 gpt Cl-27, 1 g ,200# 12/20 Brow I shut in and drop	bee Water or results of multiple completion on Well or Recompletion Report and Log form.) work. If well is directionally drille 35' of Class C cement is 7 1/2% acid. Ran GR- new perforations with pt Claymaster 5C at 4.5 or sand plus 25,300# oped from report. 11/20/2001	
 13. Describe Proposed or Cogive subsurface local 4/12/01 Moved in a plug with dump bail CCL from 3500' - 2 2200 gals. 7 1/2% bpm @ 1250 psi. 1 12/20 Super LC rest Temporary abando 14. I hereby certify that the Signed	ind rigged up on well. PC ler. Circulated well with 7 280'. Perforated at 2407 NEFE HCL containing 6 Frac'd perfs w/ 20,000 ga sin coated sand. Flowed onment applied for pendir	U pertinent details, and give pertiner cal depths for all markers and zone OH with rods and tubing. F 75 bbls 2% KCL water. Te 7, 09', 10', 13', 16', 2433' - 1 9pt Ferrotrol 270, 2 gpt Fer Is Medallion 3000 crosslini well on production. 0 BO, g further economic potenti	nt dates. including estimated date of s pertinent to this work.)* Ran 5 1/2" CIBP and set sted casing to 2200 psi. 56', 2476' - 78', 80' (31 h rrotrol 271, 2 gpt NE 940 ked CMHPG gel plus 25 0 MCFG, 105 BW. Wel ial of the well.	Date	by Water or results of multiple completion on Well or Recompletion Report and Log form.) work. If well is directionally drille 35' of Class C cement is 7 1/2% acid. Ran GR- new perforations with pt Claymaster 5C at 4.5 or sand plus 25,300# oped from report. 11/20/2001	

. —