

12. Stacks on heater-treaters/separator-dehydrators will be required to be covered to prevent mortality of avian species including neotropical migrants and bats.
13. The BLM will be informed at least two working days prior to any blasting. Notifications of blasting should include the purpose and location of the blasting, the intended date and duration of the blasting, and the estimated volume of the excavation or cut and/or fill.
14. The site will be maintained in neat and orderly condition at all times. All waste materials, both liquid and solid, shall be disposed of promptly at an appropriate, authorized waste disposal facility in accordance with all applicable State and Federal laws. "Waste" means all discarded matter including, but not limited to, human refuse, trash, garbage, debris, petroleum products, brines, chemicals, oil drums, ashes, and equipment. No waste shall be buried on site.
15. In those areas where erosion control structures are required to stabilize soil conditions, the holder shall install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound management practices. Any earth work will require prior approval by the Authorized Officer.
16. The holder shall reseed all surface disturbed by construction activities. If reseeded is required, it will be done according to the attached seeding requirements (Exhibit B), using the native seed mixture specified.
17. Upon completion of initial construction, the holder will promptly reclaim disturbed areas not necessary for continuing facility operations.
18. Closed circulation systems (steel pits) may be required on steeper slopes, on locations with restricted available area, in rocky zones where digging a pit could involve rock saws or blasting, or in other areas of special concern as determined by the BLM AO in consultation with Industry. Cuttings will be placed in permanent, lined pits, located by the BLM and Industry representatives during the initial on-site BLM-Industry meeting.

When reserve (mud) pits are used, they will be constructed as per the decisions made at the initial on-site meeting between industry and BLM. Pits will be lined with heavy (8 mil) pit liners which are never to be breached. Berms, sufficient to contain any spills or water flows and preferably made from excavated pit material, will be constructed around the pits. Relocation or reorientation of pits, or modified "v" pits, may be required at certain locations. Padding material, such as sand, dirt fines, or straw, may be required to prevent punctures in the bottom of the pit liners.

During reclamation the pits will be allowed to dry, then the liners will be folded over the pit sediments, and the pit will be backfilled. No pit will be drained and no pit liner will be broken. An examination and approval by a BLM representative will be required prior to closure of any reserve pit.
19. BLM will require prompt notification by the operator of any bit drops of four feet or more accompanied by circulation losses greater than 75 percent.
20. To minimize potential impacts to subsurface resources from well drilling, casing, or cementing, the BLM may require specific procedures, such as fresh water drilling in certain zones, special cement additives or sweeps, or cementing casing to the surface. These procedures, if required, will be determined by the BLM Fluid Minerals staff in consultation with the operator.
21. To minimize potential problems due to casing and cementing, the BLM may require the following actions as determined by BLM and the operator: