Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

N.M. O' Cons. Division 811 S. 1st Street Artesia, NM 88210-2834 eau No. 1004-0135

FORM APPROVED

March 31, 1993

5. Lease Designation and Serial No. LC 0624528-A

6. If Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well Gas 8. Well Name and No. Well Well Other White Tip 12 Federal Com #1 2. Name of Operator Nearburg Producing Company 9. API Well No. 30-015-31209 3. Address and Telephone No. 3300 North A Street, Building 2, Suite 120, Midland, Texas 79705 (915) 686-8235 10. Field and Pool, or Exploratory Area 4 Location of Well (Footage, Sec., T., R., M., or Survey Description) Revelation Morrow (Gas) 11. County or Parish, State Unit P, 660' FSL and 710' FEL, Section 12, T22S, R25E Eddy County, New Mexico CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12 TYPE OF ACTION TYPE OF SUBMISSION Abandonment Change of Plans Notice of Intent Recompletion **New Construction** X Subsequent Report Non-Routine Fracturing Plugging Back Water Shut-Off Casing Repair Conversion to Injection Altering Casing Final Abandonment Notice Other Surface Casing and Cement Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form) 13. Describe Proposed or Completed Operations (Clearly state all pertinet details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markders and zones pertinent to this work.)* 02/17/01: MIRU Patterson #18 and spud well at 0400 hrs on 02/17/01. 02/19/01: Drilled 17-1/4" hole to 305'. C&C hole. RU and ran 7 jts of 13-3/8", 48#, H40, ST&C casing to 305'. Cement casing using 94 sx 35/65 "C" poz and 200 sx "C" 2% CC. Circ 85 sx to surface. WOC 19 hrs. Cut off csg and weld on wellhead. NU BOPE and test. ACCEPTED FOR RECORD 14. I hereby certify that the foregoing is true and correct 03/07/01 Title Regulatory Analyst (This space for Federal or State office use) Date Title

