

A. P. D. (cont.)
Thirteen Point Surface Use Plan
Indian Hills Unit #24

13-3/8" Conventional centralizers , Bottom 3-joints and every 4th joint to surface.

9-5/8" Conventional centralizers middle of 1st joint, then every joint to 7500', and 1 cent. Every 4th joint thereafter to 1100'.

5. Mud Program

<u>---DEPTH---</u>		<u>MUD TYPE</u>	<u>WEIGHT</u>		<u>WL</u>		<u>VIS</u>	<u>CC</u>	<u>ADDITIVES</u>	<u>VISUAL MONTR.</u>
<u>FROM</u>	<u>TO</u>		<u>(PPG)</u>							
0	1200'	fresh water	8.3	28	N/A				Gel, Lime	Reserve
1200'	5000'	fresh	8.5	28-32	N/C				Gel, caustic, H ₂ S Scavenger	Reserve
5000'	7000'	fresh	8.9	32-36	N/C				Gel, caustic, H ₂ S Scavenger	Reserve
7000'	8800'	fresh	8.9	32-36	<20				Gel, caustic, H ₂ S Scavenger	Steel Pits

Sufficient quantities of additives will be on location to maintain above mud properties for any anticipated well conditions.

6. Logging, Testing & Coring Programs:

<u>LOG/TEST/CORE/MUDLOG/OTHER</u>	<u>--INTERVAL--</u>		<u>REMARKS</u>
	<u>FROM</u>	<u>TO</u>	
DLL/MSFL/GR/CNL/LDT/CAL	TD	5000'	
LDT/CNL/GR/CAL	TD	surf casing	
MUD LOGGER	6000'	TD	ROP, Lithology, Gas Analysis, Chromatograph
NO CORES OR DST'S			

7. Abnormal Pressures, Temperatures or Potential Hazards:

None anticipated. Possible H₂S in Cisco & Upper Penn. See H₂S Drilling Operations Plan.

8. Other Information:

Anticipated Starting Date: As soon as possible.

Duration of Well: drilling - 25 days, completion - 10 days.

This well shall be directionally drilled to a standard BHL.