

A. P. D. (cont.)
Thirteen Point Surface Use Plan
AGI # 1

Each stage will be preceded by an appropriate mud flush. Actual production hole volumes will be based on the caliper volume plus 25% excess.

Centralizer Program:

10-3/4" Conventional centralizers. Bottom 3 joints and every fourth joint to surface.

7-5/8" Conventional centralizers middle of 1st joint, then every joint to 7500', and 1 cent. Every 4th joint thereafter to 10,350'

5. Mud Program

<u>--DEPTH--</u>		<u>MUD TYPE</u>	<u>WEIGHT</u>		<u>WL</u>	<u>ADDITIVES</u>	<u>VISUAL MONTR.</u>
<u>FROM</u>	<u>TO</u>		<u>(PPG)</u>	<u>VIS</u>			
0	1200'	fresh water	8.3	28	N/A	Gel, Lime	Reserve
1200'	7000'	fresh	8.5	28-32	N/C	Gel, caustic, H ₂ S Scavenger	Reserve
7000'	7800'	fresh	8.6	32-36	N/C	Gel, caustic, H ₂ S Scavenger	Reserve
7800'	10,350'	fresh	8.6	32-36	<20	Gel, caustic, H ₂ S Scavenger	Steel Pits
10,350	11,000	fresh	8.4	32-36	< 20	Gel, caustic, H ₂ S Scavenger	Steel Pits

Sufficient quantities of additives will be on location to maintain above mud properties for any anticipated well conditions.

6. Logging, Testing & Coring Programs:

<u>LOG/TEST/CORE/MUDLOG/OTHER</u>	<u>--INTERVAL--</u>		<u>REMARKS</u>
	<u>FROM</u>	<u>TO</u>	
DLL/MSFL/GR/CNL/LDT/CAL	TD	5000'	
LDT/CNL/GR/CAL	TD	surf casing	
MUD LOGGER	6000'	TD	ROP, Lithology, Gas Analysis, Chromatograph
NO CORES OR DST'S			

7. Abnormal Pressures, Temperatures or Potential Hazards:

None anticipated. Possible H₂S in Cisco & Upper Penn. See H₂S Drilling Operations Plan.

8. Other Information: