

9. WELL SITE LAYOUT

- A. Exhibits "B-1" and "B-2" show the proposed well site layout.
- B. These exhibits indicate proposed location of the reserve pits and trash trailer.
- C. Mud pits in the active circulating system will be steel pits.
- D. The reserve pit is to be lined with a poly-ethylene liner. The pit liner will be a minimum of 6 mils thick. The pit liner will extend a minimum of 2'00" over the reserve pit dikes where the liner will be anchored down.
- E. The reserve pit will be fenced on three sides with four strands of barbed wire during drilling and completion phases. The fourth side will be fenced after all drilling operations have ceased. If the well is a producer, the reserve pit fence will be torn down. The reserve pit and those areas of the location not essential to production facilities will be reclaimed and seeded per BLM requirements.

10. PLANS FOR RESTORATION OF SURFACE

Rehabilitation of the location and reserve pit will start in a timely manner after all drilling operations cease. The type of reclamation will depend on whether the well is a producer or dry hole.

In either event, the reserve pit will be allowed to dry properly, and fluid removed and disposed of in accordance with Article 7.B as previously noted. The pit area will then be leveled and contoured to conform to the original and surrounding area as closely as is possible. Drainage system, if any, will be reshaped to the original configuration with provisions made to alleviate erosion. These may need to be modified in certain circumstance to prevent inundation of the location pad and surface facilities. After the area had been shaped and contoured, topsoil from the soil pits will be placed over the disturbed area to the extent possible. Revegetation procedures will comply with BLM standards.

Should the well be a producer, the previously noted procedures will apply to those areas which are not required for production facilities.