

- E. Garbage and trash produced during drilling or completion operations will be disposed in a separate trash trailer on location. All waste material will be contained to prevent scattering by the wind. All water and fluids will be disposed into the reserve pit. Salts and other chemicals produced during drilling or testing will be disposed into the reserve pit. No toxic waste or hazardous chemicals will be produced by the operation.
- F. After the rig is moved out and the proposed well is either completed or abandoned, all waste materials will be removed within 30 days. No adverse materials will be left on the location. The reserve pit will be completely fenced and kept closed until dried. When the reserve pit is dry enough to breakout and fill, and as weather permits, the unused portion of the wellsite will be leveled and reseeded as per BLM specifications. Only that part of the pad required for production facilities will remain in use. In the event of a dry hole, only a dry hole marker will remain.

8. Ancillary Facilities:

No airstrip, campsite or other facility will be built as a result of the operations of the proposed well.

9. Well Site Layout:

- A. The drill pad layout with elevations, as staked by Dan R. Reddy, Engineer, is shown on Exhibit "D". Dimensions of the pad, pits and location of major rig components are shown. Top soil, if available, will be stockpiled per BLM specifications as determined at the on-site inspection. Since the pad is fairly level, no major cuts will be required.
- B. The planned orientation of the rig and associated drilling equipment, reserve pit, trash pit, pipe racks, turn-around and parking areas, and access road are shown on Exhibit "D". No permanent living facilities are planned, however, a temporary foreman/toolpusher's trailer will be on location during drilling operations.