

5. Minimum Specifications for Pressure Control:

The blowout preventer equipment (BOP) shown on Exhibit "A" will consist of a double ram-type (3000 psi WP) preventer and a bag-type (hydril) preventer (3000 psi WP). Both units will be hydraulically operated and the ram-type preventer will be equipped with blind rams on top and 4 1/2" drill pipe rams on bottom. Both BOPs will be nipped up on the 13 3/8" surface casing and used continuously until TD is reached. All BOPs and accessory equipment will be tested to 1000 psi before drilling out of surface casing. Before drilling out of surface casing, the ram-type BOP and accessory equipment will be tested to 3000 psi and the hydril to 70% of rated working pressure (2100 psi).

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. A 2" kill line and 3" choke line will be included in the drilling spool located below the ram-type BOP. Other accessories to the BOP equipment will include a kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold with 3000 psi WP rating.

6. Types and Characteristics of the Proposed Mud System:

0' to 400'	Native mud consisting of fresh water with lime, gel paper and fiber will be utilized.
400' to 2700'	Saturated brine water <i>Fresh Water</i> purchased from commercial sources with paper and fiber will be utilized.
2700' to 3500'	2% to 3% KCL with 20-5 PPM Nitrates, caustic, paper and starch will be used to maintain approximately 28-30 viscosity and <50 water loss. Anticipated mud properties are MW 8.5-8.9, PH 9-10, CL 50,000.