

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-015-31582

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
V-4804

7. Lease Name or Unit Agreement Name
Tracy AXW State

8. Well No.
1

9. Pool name or Wildcat
Undes. Burton Flat Morrow

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3127' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location BHL: 660' FNL & 660' FEL of Sec. 36-T21S-R26E (Unit A, NENE)
Unit Letter I : 1650 Feet From The South Line and 660 Feet From The East Line
Section 25 Township 21S Range 26E NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: Spud, conductor, resume drilling, surface casing & cement <input checked="" type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 12-1/4" hole with rat hole machine at 10:00 AM 1-31-2001. NOTE: Notified Mike Stubblefield w/OCD-Artesia of spud. Drilled conductor hole to 40' and reamed 12-1/4" hole to 26" from surface to 40'. Set 40' of 20" conductor pipe. Cemented to surface. Resumed drilling a 17-1/2" hole with rotary tools at 10:30 PM 2-17-2001.

TD 607'. Reached TD at 10:30 PM 2-18-2001. Ran 14 joints of 13-3/8" 48# H-40 (610.13') of casing set at 607'. 1-Texas Pattern notched guide shoe set at 607'. Insert float set at 562'. Cemented with 200 sacks "H", 10% A-10B, 10#/bbl LCM 1, 1/4#/sack celloflake and 1% CaCl2 (yield 1.52, weight 14.6) and 400 sacks BJ Lite C (65-35-6), 5#/bbl LCM 1, and 2% CaCl2 (yield 1.88, weight 12.7). Tailed in with 200 sacks Class C and 2% CaCl2 (yield 1.34, weight 14.8). PD 5:30 AM 2-19-2001. Bumped plug to 800 psi, float did not hold. Left head on casing for 6 hours to allow cement to set up. Circulated 200 sacks. WOC. Cut off and welded on flow nipple. Drilled out at 1:30 AM 2-20-2001. WOC 20 hours. Reduced hole to 12-1/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE July 12, 2001
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY TONY W. GUM
DISTRICT II SUPERVISOR

JUL 30 2001

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: