

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.  
30-015-31582

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.  
V-4804

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. Name of Operator  
YATES PETROLEUM CORPORATION

3. Address of Operator  
105 South 4th St., Artesia, NM 88210

4. Well Location BHL: 660' FNL & 660' FEL of Sec. 36-T21S-R26E (Unit A, NENE)  
Unit Letter I : 1650 Feet From The South Line and 660 Feet From The East Line  
Section 25 Township 21S Range 26E NMMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
3127' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: Intermediate casing & cement <input checked="" type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 2377'. Reached TD at 1:30 PM 2-24-2001. Ran 53 joints of 9-5/8" 36# J-55 (2380.76') of casing set at 2377'. 1-Texas Pattern notched guide shoe set at 2377'. Float collar set at 2332'. Cemented with 200 sacks Class H, 10% A-10B, 1/4#/sack celloflake, 10#/sack gilsonite and 1% CaCl<sub>2</sub> (yield 1.52, weight 14.6) and 900 sacks Class C (65-35-6), 1/4#/sack celloflake, 5#/sack gilsonite and 2% CaCl<sub>2</sub> (yield 1.89, weight 12.7). Tailed in with 200 sacks Class C with 2%CaCl<sub>2</sub> (yield 1.34, weight 14.8). PD 2:00 AM 2-25-2001. Bumped plug to 1770#, OK. Circulated 193 sacks. WOC. Nippled up and tested to 1000# for 15 minutes, OK. Drilled out at 4:30 AM 2-26-2001. WOC 26-1/2 hours. Reduced hole to 8-3/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE July 12, 2001

TYPE OR PRINT NAME Rusty Klein

TELEPHONE NO. 505/748-1471

(This space for State Use) ORIGINAL SIGNED BY TIM W. GUM  
DISTRICT II SUPERVISOR

JUL 30 2001

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: