

YATES PETROLEUM CORPORATION
Tracy AXW State #1
Section 25-T21S-R26E
Eddy County, New Mexico

#27: ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.:

<u>DEPTH INTERVAL</u>	<u>TREATMENT</u>
11876-11900'	Acidized with 1500 gallons 7-1/2% Morrow acid & 1000 scf/bbl N2 and ball sealers Squeezed with 100 sacks Class H, .3% D-167, .2% D-65 and .1% D-13. Tailed in with 100 sacks Class H, .2% D-13. Squeezed to 3700#
11800-11802'	Acidized with 250 gallons of 7-1/2% Morrow acid
11725-11732'	Acidized with 500 gallons 7-1/2% Morrow acid - communicated with 9 bbls pumped
11705-11711'	Pumped 5 bbls 7-1/2% Morrow acid - communicated
11660-11668'	Pumped 5 bbls 7-1/2% Morrow acid - communicated
11632-11641'	Acidized with 500 gallons of 7-1/2% Morrow acid
11595-11597'	Acidized with 500 gallons of 7-1/2% Morrow acid
11595-11802'	Acidized with 1350 gallons of 7-1/2% Morrow acid Frac'd with 24,948 gallons of 65Q CO2 foam and 75500# 20-40 interprop
11460-11466'	Acidized with 1500 gallons of 7-1/2% Morrow acid and 1500 scf/bbl N2