

Tracy2.txt

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	CLOSURE Distance FT	CLOSURE Direction Deg	Dogleg Severity Deg/100
7868.86	27.00	230.34	7325.93	-1470.57	-1773.72	2304.05	2304.05	230.34	.00
7968.86	27.00	230.34	7415.03	-1499.55	-1808.67	2349.45	2349.45	230.34	.00
8068.86	27.00	230.34	7504.13	-1528.52	-1843.62	2394.85	2394.85	230.34	.00
8168.86	27.00	230.34	7593.23	-1557.50	-1878.56	2440.25	2440.25	230.34	.00
8268.86	27.00	230.34	7682.33	-1586.48	-1913.51	2485.65	2485.65	230.34	.00
8368.86	27.00	230.34	7771.43	-1615.45	-1948.46	2531.05	2531.05	230.34	.00
8468.86	27.00	230.34	7860.53	-1644.43	-1983.41	2576.45	2576.45	230.34	.00
8568.86	27.00	230.34	7949.63	-1673.41	-2018.36	2621.85	2621.85	230.34	.00
8668.86	27.00	230.34	8038.74	-1702.38	-2053.31	2667.24	2667.24	230.34	.00
8768.86	27.00	230.34	8127.84	-1731.36	-2088.26	2712.64	2712.64	230.34	.00
8868.86	27.00	230.34	8216.94	-1760.33	-2123.21	2758.04	2758.04	230.34	.00
8968.86	27.00	230.34	8306.04	-1789.31	-2158.16	2803.44	2803.44	230.34	.00
9068.86	27.00	230.34	8395.14	-1818.29	-2193.11	2848.84	2848.84	230.34	.00
9168.86	27.00	230.34	8484.24	-1847.26	-2228.06	2894.24	2894.24	230.34	.00
9268.86	27.00	230.34	8573.34	-1876.24	-2263.01	2939.64	2939.64	230.34	.00
9321.23	27.00	230.34	8620.00	-1891.41	-2281.31	2963.41	2963.41	230.34	.00
STOP AND RUN 7" CASING. AFTER RUNNING 7" CASING TIE W/ 6 1/8" BIT AND RESUME DRILLING, STILL HOLDING 27 DEG. ANGLE.									
9368.86	27.00	230.34	8662.44	-1905.21	-2297.96	2985.04	2985.04	230.34	.00
9468.86	27.00	230.34	8751.54	-1934.19	-2332.91	3030.44	3030.44	230.34	.00
9568.86	27.00	230.34	8840.64	-1963.17	-2367.86	3075.84	3075.84	230.34	.00
9668.86	27.00	230.34	8929.74	-1992.14	-2402.80	3121.23	3121.23	230.34	.00
9768.86	27.00	230.34	9018.84	-2021.12	-2437.75	3166.63	3166.63	230.34	.00
9868.86	27.00	230.34	9107.94	-2050.10	-2472.70	3212.03	3212.03	230.34	.00
9968.86	27.00	230.34	9197.04	-2079.07	-2507.65	3257.43	3257.43	230.34	.00
10068.86	27.00	230.34	9286.14	-2108.05	-2542.60	3302.83	3302.83	230.34	.00
10168.86	27.00	230.34	9375.25	-2137.02	-2577.55	3348.23	3348.23	230.34	.00
10268.86	27.00	230.34	9464.35	-2166.00	-2612.50	3393.63	3393.63	230.34	.00
10368.86	27.00	230.34	9553.45	-2194.98	-2647.45	3439.03	3439.03	230.34	.00
10387.18	27.00	230.34	9569.77	-2200.28	-2653.85	3447.34	3447.34	230.34	.00
BEGIN DROPPING ANGLE AT A RATE OF 5 DEGREES/100'									
10417.18	25.50	230.34	9596.67	-2208.75	-2664.07	3460.61	3460.61	230.34	5.00
10447.18	24.00	230.34	9623.91	-2216.77	-2673.73	3473.17	3473.17	230.34	5.00
10477.18	22.50	230.34	9651.48	-2224.33	-2682.85	3485.01	3485.01	230.34	5.00
10507.18	21.00	230.34	9679.34	-2231.42	-2691.41	3496.13	3496.13	230.34	5.00
10537.18	19.50	230.34	9707.49	-2238.05	-2699.40	3506.51	3506.51	230.34	5.00
10567.18	18.00	230.34	9735.89	-2244.20	-2706.82	3516.16	3516.16	230.34	5.00
10597.18	16.50	230.34	9764.54	-2249.88	-2713.67	3525.05	3525.05	230.34	5.00
10627.18	15.00	230.34	9793.42	-2255.08	-2719.94	3533.19	3533.19	230.34	5.00
10657.18	13.50	230.34	9822.49	-2259.79	-2725.63	3540.58	3540.58	230.34	5.00
10687.18	12.00	230.34	9851.75	-2264.02	-2730.72	3547.20	3547.20	230.34	5.00
10717.18	10.50	230.34	9881.17	-2267.75	-2735.23	3553.05	3553.05	230.34	5.00
10747.18	9.00	230.34	9910.74	-2271.00	-2739.14	3558.13	3558.13	230.34	5.00