

Countclb.txt

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	CLOSURE Distance FT	CLOSURE Direction Deg	Dogleg Severity Deg/100
7138.77	25.00	301.80	6747.18	962.72	-1552.95	1827.15	1827.15	301.80	.00
7238.77	25.00	301.80	6837.81	984.98	-1588.87	1869.41	1869.41	301.80	.00
7338.77	25.00	301.80	6928.44	1007.25	-1624.79	1911.67	1911.67	301.80	.00
7438.77	25.00	301.80	7019.07	1029.52	-1660.71	1953.94	1953.94	301.80	.00
7538.77	25.00	301.80	7109.70	1051.79	-1696.63	1996.20	1996.20	301.80	.00
7638.77	25.00	301.80	7200.34	1074.05	-1732.55	2038.46	2038.46	301.80	.00
7738.77	25.00	301.80	7290.97	1096.32	-1768.47	2080.72	2080.72	301.80	.00
7838.77	25.00	301.80	7381.60	1118.59	-1804.39	2122.98	2122.98	301.80	.00
7938.77	25.00	301.80	7472.23	1140.86	-1840.31	2165.24	2165.24	301.80	.00
8038.77	25.00	301.80	7562.86	1163.12	-1876.23	2207.51	2207.51	301.80	.00
8138.77	25.00	301.80	7653.49	1185.39	-1912.15	2249.77	2249.77	301.80	.00
8238.77	25.00	301.80	7744.12	1207.66	-1948.07	2292.03	2292.03	301.80	.00
8338.77	25.00	301.80	7834.75	1229.93	-1983.99	2334.29	2334.29	301.80	.00
8438.77	25.00	301.80	7925.38	1252.19	-2019.91	2376.55	2376.55	301.80	.00
8538.77	25.00	301.80	8016.01	1274.46	-2055.83	2418.82	2418.82	301.80	.00
8638.77	25.00	301.80	8106.64	1296.73	-2091.75	2461.08	2461.08	301.80	.00
8738.77	25.00	301.80	8197.27	1319.00	-2127.67	2503.34	2503.34	301.80	.00
8838.77	25.00	301.80	8287.90	1341.26	-2163.58	2545.60	2545.60	301.80	.00
8938.77	25.00	301.80	8378.54	1363.53	-2199.50	2587.86	2587.86	301.80	.00
9038.77	25.00	301.80	8469.17	1385.80	-2235.42	2630.12	2630.12	301.80	.00
9138.77	25.00	301.80	8559.80	1408.07	-2271.34	2672.39	2672.39	301.80	.00
RUN 7" CASING AT 8,620' TVD. AFTER SETTING CASING RESUME DRILLING 6 1/8" HOLE, STILL HOLDING 25 DEG ANGLE.									
9205.20	25.00	301.80	8620.00	1422.86	-2295.20	2700.46	2700.46	301.80	.00
9238.77	25.00	301.80	8650.43	1430.33	-2307.26	2714.65	2714.65	301.80	.00
9338.77	25.00	301.80	8741.06	1452.60	-2343.18	2756.91	2756.91	301.80	.00
9438.77	25.00	301.80	8831.69	1474.87	-2379.10	2799.17	2799.17	301.80	.00
9538.77	25.00	301.80	8922.32	1497.14	-2415.02	2841.43	2841.43	301.80	.00
9638.77	25.00	301.80	9012.95	1519.40	-2450.94	2883.70	2883.70	301.80	.00
9738.77	25.00	301.80	9103.58	1541.67	-2486.86	2925.96	2925.96	301.80	.00
9838.77	25.00	301.80	9194.21	1563.94	-2522.78	2968.22	2968.22	301.80	.00
9936.58	25.00	301.80	9282.86	1585.72	-2557.91	3009.56	3009.56	301.80	.00
BEGIN DROPPING ANGLE AT A RATE OF 3 DEGREES/100'									
9966.58	24.10	301.80	9310.15	1592.29	-2568.51	3022.02	3022.02	301.80	3.00
9996.58	23.20	301.80	9337.63	1598.63	-2579.74	3034.05	3034.05	301.80	3.00
10026.58	22.30	301.80	9365.29	1604.74	-2588.60	3045.66	3045.66	301.80	3.00
10056.58	21.40	301.80	9393.14	1610.62	-2598.09	3056.82	3056.82	301.80	3.00
10086.58	20.50	301.80	9421.15	1616.27	-2607.20	3067.55	3067.55	301.80	3.00
10116.58	19.60	301.80	9449.33	1621.69	-2615.94	3077.83	3077.83	301.80	3.00
10146.58	18.70	301.80	9477.67	1626.88	-2624.31	3087.67	3087.67	301.80	3.00
10176.58	17.80	301.80	9506.16	1631.83	-2632.29	3097.07	3097.07	301.80	3.00
10206.58	16.90	301.80	9534.80	1636.54	-2639.90	3106.01	3106.01	301.80	3.00
10236.58	16.00	301.80	9563.57	1641.02	-2647.12	3114.51	3114.51	301.80	3.00