 13. Describe Proposed or Completed Operations (Clearly state all pertinent detaus, and give pertinent dates, including estimated date of starting any proposed work. If well give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 1. Amend APD to utilize 13-5/8" 3000# annular preventer to drill 12-1/4" intermediate hole. 2. Amend APD to pressure test 11" 3000# BOPE with rig pump to 1500 psig, prior to drilling into the Wolfcamp formation at 8500' or upon first bit trip prior to 8000', the BOP, choke manifold and 200' of 9-5/8" casing will be hydrotested.
Subsequent Report Subsequent Report Plugging Back Plugging Back Non-Routine Fract Casing Repair Altering Casing Other Other Dispose Water Noie: Report results of mult Conversion to Injee Other Dispose Water Noie: Report results of mult Completed Operations (Clearly state all pertunent details, and give pertunent dates, including estimated date of starting any proposed work. If well completion or Recompletion Completion Completion or Recompletion Completion Completin Completion Completion Complet
Final Abandonment Notice Casing Repair Water Shut-Off Conversion to Inje Other Dispose Water II. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well completion or Recompletion II. Amend APD to utilize 13-5/8" 3000# annular preventer to drill 12-1/4" intermediate hole. 2. Amend APD to pressure test 11" 3000# BOPE with rig pump to 1500 psig, prior to drilling into the Wolfcamp formation at 8500' or upon first bit trip prior to 8000', the ROB schedure prior bit is a schedule prior to drilling into the Wolfcamp formation at 8500' or upon first bit trip prior to 8000', the ROB schedure prior bit is a schedule prior bit work is a schedule prior bit is a schedule prio
TYPE OF SUBMISSION TYPE OF ACTION Image: Change of Intent Image: Change of Plans Image: Chang
Notice of Intent Subsequent Report Final Abandonment Notice Abandonment Recompletion Plugging Back Final Abandonment Notice Altering Casing Other Dispose Water (Note: Report results of multice starting any proposed work. If well give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 1. Amend APD to utilize 13-5/8" 3000# annular preventer to drill 12-1/4" intermediate hole. 2. Amend APD to pressure test 11" 3000# BOPE with rig pump to 1500 psig, prior to drilling into the Wolfcamp formation at 8500" or upon first bit trip prior to 8000! the POP abele mark for the p
Notice of Intent Subsequent Report Final Abandonment Notice
TYPE OF SUBMISSION TYPE OF ACTION Image: Notice of Intent Image: Abandonment Image: Change of Plans Image: Subsequent Report Image: Plugging Back Image: Non-Routine Fract Image: Final Abandonment Notice Image: Plugging Back Image: Non-Routine Fract Image: Subsequent Report Image: Plugging Back Image: Non-Routine Fract Image: Final Abandonment Notice Image: Plugging Back Image: Non-Routine Fract Image: Subsequent Report Image: Plugging Back Image: Plugging Back Image: Subsequent Report Image: Plugging Back Image: Plugging Back Image: Proposed or Completed Operations (Clearly state all pertiment detaus, and give pertiment dates, including estimated date of starting any proposed work. If well give subsurface locations and measured and true vertical depths for all markers and zones pertiment to this work.)* 1. Amend APD to utilize 13-5/8" 3000# annular preventer to drill 12-1/4" intermediate hole. 2. Amend APD to pressure test 11" 3000# BOPE with rig pump to 1500 psig, prior to drilling into the Wolfcamp formation at 8500' or upon first bit trip prior to 8000!
TYPE OF SUBMISSION TYPE OF ACTION Image: Notice of Intent Image: Abandonment Image: Change of Plans Image: Subsequent Report Image: Plugging Back Image: Non-Routine Fract Image: Final Abandonment Notice Image: Plugging Back Image: Non-Routine Fract Image: Proposed or Completed Operations (Clearly state all pertiment detaus, and give pertiment dates, including estimated date of starting any proposed work. If well give subsurface locations and measured and true vertical depths for all markers and zones pertiment to this work.)* 1. Amend APD to utilize 13-5/8" 3000# annular preventer to drill 12-1/4" intermediate hole. 2. Amend APD to pressure test 11" 3000# BOPE with rig pump to 1500 psig, prior to drilling into the Wolfcamp formation at 8500' or upon first bit trip prior to 8000!
TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment X Change of Plans Subsequent Report Plugging Back Non-Routine Fract Final Abandonment Notice Plugging Back Non-Routine Fract Other Other Dispose Water Note: Report results of multice Other Dispose Water Note: Report results of multice Non-Routine Fract Non-Routine Fract Describe Proposed or Completed Operations (Clearly state all pertinent detaus, and give pertinent dates, including estimated date of starting any proposed work. If well give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 1. Amend APD to utilize 13-5/8" 3000# annular preventer to drill 12-1/4" intermediate hole. 2. Amend APD to pressure test 11" 3000# BOPE with rig pump to 1500 psig, prior to drilling into the Wolfcamp formation at 8500' or upon first bit trip prior to 8000!
TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment X Change of Plans Subsequent Report Plugging Back Non-Routine Fract Final Abandonment Notice Plugging Back Non-Routine Fract Other Other Dispose Water Note: Report results of multice Other Dispose Water Note: Report results of multice Non-Routine Fract Non-Routine Fract Describe Proposed or Completed Operations (Clearly state all pertinent detaus, and give pertinent dates, including estimated date of starting any proposed work. If well give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 1. Amend APD to utilize 13-5/8" 3000# annular preventer to drill 12-1/4" intermediate hole. 2. Amend APD to pressure test 11" 3000# BOPE with rig pump to 1500 psig, prior to drilling into the Wolfcamp formation at 8500' or upon first bit trip prior to 8000!
Notice of Intent Abandonment Abandonment Abandonment Abandonment Abandonment Abandonment Abandonment Active Subsequent Report Final Abandonment Notice Altering Casing Other Conversion to Injee Other Dispose Water (Note: Report results of mult Completed Operations (Clearly state all pertunent detaus, and give pertunent dates, including estimated date of starting any proposed work. If weil give subsurface locations and measured and true vertical depths for all markers and zones pertunent to this work.)* Amend APD to utilize 13-5/8" 3000# annular preventer to drill 12-1/4" intermediate hole. Amend APD to pressure test 11" 3000# BOPE with rig pump to 1500 psig, prior to drilling into the Wolfcamp formation at 8500' or upon first bit trip prior to 8000! the ROP abales period to the
Image: Construction Image: Constructi
Image: Construction Image: Constructi
Subsequent Report Recompletion New Construction Final Abandonment Notice Plugging Back Non-Routine Fract Gasing Repair Water Shut-Off Other Dispose Water (Mose: Report results of multice give subsurface locations and measured and true verucal depths for all markers and zones pertunent to this work.)* Dispose Water intermediate hole. Amend APD to utilize 13-5/8" 3000# annular preventer to drill 12-1/4" intermediate hole. Amend APD to pressure test 11" 3000# BOPE with rig pump to 1500 psig, prior to drilling into the Wolfcamp formation at 8500' or upon first bit trip prior to 8000!
Subsequent Report Recompletion New Construction Final Abandonment Notice Plugging Back Non-Routine Fract Gescribe Proposed or Completed Operations (Clearly state all pertunent details, and give pertunent dates, including estimated date of starting any proposed work. If well give subsurface locations and measured and true vertical depths for all markers and zones pertunent to this work.)* 1. Amend APD to utilize 13-5/8" 3000# annular preventer to drill 12-1/4" intermediate hole. 2. Amend APD to pressure test 11" 3000# BOPE with rig pump to 1500 psig, prior to drilling into the Wolfcamp formation at 8500' or upon first bit trip prior to 8000! the ROP abala correction of the depth of the trip prior to 8000!
 Subsequent Report Subsequent Report Final Abandonment Notice Piugging Back Casing Repair Altering Casing Other Dispose Water (Note: Report results of multiple of the completion of Recompletion of Recompletion Describe Proposed or Completed Operations (Clearly state all pertunent details, and give pertunent dates, including estimated date of starting any proposed work. If well give subsurface locations and measured and true vertical depths for all markers and zones pertunent to this work.)* Amend APD to utilize 13-5/8" 3000# annular preventer to drill 12-1/4" intermediate hole. Amend APD to pressure test 11" 3000# BOPE with rig pump to 1500 psig, prior to drilling into the Wolfcamp formation at 8500' or upon first bit trip prior to 8000' the ROP obsise marifesion is a specific date of the proposed of the prior to drilling into the Wolfcamp formation at 8500' or upon first bit trip prior to 8000' the ROP obsise marifesion of the proposed to the prior to drilling into the Wolfcamp formation at 8500' or upon first bit trip prior to 8000' the ROP obsise marifesion of the proposed to the prior to the specific date of the prior to drilling into the wolfcamp formation at 8500' or upon first bit trip prior to 8000' the ROP obsise marifesion of the prior to 4000' the prior
Subsequent Report Subsequent Report Final Abandonment Notice Final Aba
Final Abandonment Notice Final Abandonment Not
Final Abandonment Notice Final Abandonment Notice Altering Casing Conversion to Injee Conversion to Injee Dispose Water (Note: Report results of mul Completion of Recompletion spive subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Amend APD to utilize 13-5/8" 3000# annular preventer to drill 12-1/4" intermediate hole. Amend APD to pressure test 11" 3000# BOPE with rig pump to 1500 psig, prior to drilling into the Wolfcamp formation at 8500' or upon first bit trip prior to 8000! the ROB obels mariful to the
 Final Abandonment Notice Altering Casing Other Dispose Water (Note: Report results of multicomportance) Describe Proposed or Completed Operations (Clearly state all pertunent details, and give pertunent dates, including estimated date of starting any proposed work. If well give subsurface locations and measured and true vertical depths for all markers and zones pertunent to this work.)* Amend APD to utilize 13-5/8" 3000# annular preventer to drill 12-1/4" intermediate hole. Amend APD to pressure test 11" 3000# BOPE with rig pump to 1500 psig, prior to drilling into the Wolfcamp formation at 8500' or upon first bit trip prior to 8000! the POR obels perior folded is 000!
Conversion to inject of the proposed or Completed Operations (Clearly state all pertunent details, and give pertunent dates, including estimated date of starting any proposed work. If well give subsurface locations and measured and true vertical depths for all markers and zones pertunent to this work.)* Amend APD to utilize 13-5/8" 3000# annular preventer to drill 12-1/4" intermediate hole. Amend APD to pressure test 11" 3000# BOPE with rig pump to 1500 psig, prior to drilling into the Wolfcamp formation at 8500' or upon first bit trip prior to 8000! the BOP obles period to the solution of the so
 Other Dispose Water (Note: Report results of multicompletion or Recompletion or Recompleti
 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Amend APD to utilize 13-5/8" 3000# annular preventer to drill 12-1/4" intermediate hole. Amend APD to pressure test 11" 3000# BOPE with rig pump to 1500 psig, prior to drilling into the Wolfcamp formation at 8500' or upon first bit trip prior to 8000! the POR obele marifed is a solution of the solution.
 (Note: Report results of multiplication of Recompletion of Recomp
 Describe Proposed or Completed Operations (Clearly state all pertunent details, and give pertunent dates, including estimated date of starting any proposed work. If well give subsurface locations and measured and true vertical depths for all markers and zones pertunent to this work.)* 1. Amend APD to utilize 13-5/8" 3000# annular preventer to drill 12-1/4" intermediate hole. 2. Amend APD to pressure test 11" 3000# BOPE with rig pump to 1500 psig, prior to drilling into the Wolfcamp formation at 8500" or upon first bit trip prior to 8000! the ROP obside environment of the solution of the s
 Describe Proposed or Completed Operations (Clearly state all pertunent details, and give pertunent dates, including estimated date of starting any proposed work. If well give subsurface locations and measured and true vertical depths for all markers and zones pertunent to this work.)* 1. Amend APD to utilize 13-5/8" 3000# annular preventer to drill 12-1/4" intermediate hole. 2. Amend APD to pressure test 11" 3000# BOPE with rig pump to 1500 psig, prior to drilling into the Wolfcamp formation at 8500' or upon first bit trip prior to 8000! the ROP obside environment of the solution of the s
 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 1. Amend APD to utilize 13-5/8" 3000# annular preventer to drill 12-1/4" intermediate hole. 2. Amend APD to pressure test 11" 3000# BOPE with rig pump to 1500 psig, prior to drilling into the Wolfcamp formation at 8500' or upon first bit trip prior to 8000! the ROP ebsite environment of the solution of the s
 Amend APD to utilize 13-5/8" 3000# annular preventer to drill 12-1/4" intermediate hole. Amend APD to pressure test 11" 3000# BOPE with rig pump to 1500 psig, prior to drilling into the Wolfcamp formation at 8500' or upon first bit trip prior to 8000! the BOP abake prior 1 and 1
 Amend APD to utilize 13-5/8" 3000# annular preventer to drill 12-1/4" intermediate hole. Amend APD to pressure test 11" 3000# BOPE with rig pump to 1500 psig, prior to drilling into the Wolfcamp formation at 8500' or upon first bit trip prior to 8000! the BOP abele armiful at 1000#
 Amend APD to utilize 13-5/8" 3000# annular preventer to drill 12-1/4" intermediate hole. Amend APD to pressure test 11" 3000# BOPE with rig pump to 1500 psig, prior to drilling into the Wolfcamp formation at 8500' or upon first bit trip prior to 8000! the BOP abele profile is a sector.
2. Amend APD to pressure test 11" 3000# BOPE with rig pump to 1500 psig, prior to drilling into the Wolfcamp formation at 8500' or upon first bit trip prior to 8000! the BOP abele prior to 2001.
2. Amend APD to pressure test 11" 3000# BOPE with rig pump to 1500 psig, prior to drilling into the Wolfcamp formation at 8500' or upon first bit trip prior to 8000! the BOP abele prior to 2001.
I hereby certify that the foregoing is true and correct
Signed Title Drilling and Production Engineer Date 03/30/01
(This space for Federal or State office use)
Signed Gring and Production Engineer Date (This space for Federal or State office user (ODIC SCD) ALEXIS C SWORDDA



·