

Submit 3 Copies to Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Geology, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION

2040 South Pacheco
Santa Fe, NM 87505

WELL API NO.

30-015-31770

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Artemian "6P" State Com.
(28044)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☐ Other ☒ proposed gas well

2. Name of Operator

(20305)

Devon -SFS Operating, Inc. ✓

Wally Frank

8. Well No.

1

3. Address of Operator

20 N. Broadway, Suite 1500

Oklahoma City, OK 73102

Sr. Operations Engr.

(405) 552-4595

9. Pool name or Wildcat

Happy Valley (Morrow) (78060)

4. Well Location

Unit Letter P : 720 feet from the south line and 800 feet from the east line

Section 6

Township 22S

Range 26E

NMPM

County Eddy, NM

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

GL 3608', DF 3624', KB 3625'

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOBS ☐

OTHER: casing strings, logging, WOCU ☒

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work). SEE RULE 1103. For Multiple Completions: Attach diagram of proposed completion or recompletion.

This well spud on 10-08-2001 at 0230 hrs. Drld 17 1/2" hole to 508'. On 10-10-2001 ran 12 jts 13 3/8" 48# H-40 ST&C casing, set at 508'; cemented with 150 sx Thickset/Class H; TOC at 420' by Temp Svy; topped with 450 sx Class C; TOC at surface. WOC 19 hrs.

Drld 12 1/4" hole to 2420'. On 10-18-2001 ran 54 jts 9 5/8" 40# J-55 LT&C casing, set at 2416 with ECP DV tool at 1457'; cemented thru DV tool with 325 sx Class C + 225 sx 35/65/6 Poz/Class C + 200 sx Class C; TOC at 600' by Temp Svy; topped with 225 sx Class C; TOC at surface. WOC 37 hrs.

Drld 8 5/8" hole to 9955'. On 11-04-2001 Schlumberger 1st run Platform Express Azimuthal Laterlog/MCFL/NGT and Density/Neutron logs.

(Continued on the reverse.)

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Candace R. Graham TITLE Engineering Tech.

DATE 03/12/2002

Type or print name Candace R. Graham X4520

Telephone No. (405)235-3611

(This space for State use)

APPROVED BY [Signature] **ORIGINAL SIGNED BY TIM W. GUM**
DISTRICT # SUPERVISOR TITLE

DATE

Conditions of approval, if any:

APR 01 2002

(Continued from the front.)

Ran 243 jts 7" 26# P-110 LT&C casing on 11-05-2001, set at 9951'; cemented with 350 sx 15/61/11 Poz C + 300 sx Class H; WOC 42 hrs. Drid cement 9851-9955'.

Drid 6 1/4" hole. Reached TD 11,550' at 0330 hrs on 11-14-2001. Worked to free pipe and reamed. On 11-17-2001 Schlumberger 2nd run Platform Express Azimuthal Laterlog/MCFL/NGT and Density/Neutron logs.

Ran 42 jts 4 1/2" 11.6# L-80 LT&C liner on 11-18-2001, set 9643-11,548'; cemented with 250 sx Class H; WOC 16 hrs. Drid cement 9382-9643' (top of liner).

Released rig at 0300 hrs 11-20-2001. WOCU.