

dried. When the reserve pit is dry enough to breakout and fill and, as weather permits, the unused portion of the well site will be leveled and reseeded as per BLM specifications. Only that part of the pad required for production facilities will be kept in use. In the event of dry hole only a dry hole marker will remain.

7. Ancillary Facilities:

No airstrip, campsite, or other facilities will be built as a result of the operations on this well.

8. Well Site Layout:

- A) The drill pad layout in Exhibit H, with elevations staked by Basin Survey's shown in Exhibit B. Dimensions of the pad and pits and location of major rig components are shown. Top soil, if available, will be stockpiled per BLM specifications as determined at the on-site inspection. Because the pad is almost level no major cuts will be required.
- B) Exhibit H shows the planned orientation for the rig and associated drilling equipment, reserve pit, trash pit, pipe racks, turn-around and parking areas and access road. No permanent living facilities are planned but a temporary foreman/toolpusher's trailer will be on location during the drilling operations.
- C) The reserve pit will be lined with a high-quality plastic sheeting (5-7 mil thickness).

9. Plans for Restoration of the Surface:

- A) Upon completion of the proposed operations, if the well is to be abandoned, the caliche will be plowed and reseeded. The pit area, after allowing to dry, will be broken out and leveled. The original top soil will be returned to the entire location which will be leveled and contoured to as nearly the original topography as possible as shown in Exhibit C.

All trash, garbage and pit lining will be buried or hauled away in order to leave the location in an aesthetically pleasing condition. All pits will be filled and the location leveled within 120 days after abandonment.