

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.
30-015-32000

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

Lucy ALC State

7. Well No.

8. Pool name or Wildcat
Lost Tank Delaware

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter G : 1980 feet from the North line and 2080 feet from the East line

Section 34 Township 21S Range 31E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3488' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

OTHER:

☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Perforate and Stimulate

☒

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

10/21/02 - TIH to 8270'. Drilled cement to float collar at 8286'. Circulated hole clean. Pickled tubing with 850 gal 15% NEFE acid. Displaced hole with 3% KCL.

10/22/02 - Ran GR/CCL/CBL from PBTD to 8273' to cement top of 5584'. Ran log at DV tool at 4063'. Cement top at 130'. Perforate Basal Brushy Canyon 7858'-7866' (9 holes), 7880'-7888' (5 holes), 7928'-7934' (7 holes), 8014'-8026' (13 holes).

10/24/02 - Frac 7858'-8026' with 125,348 20/40 Super LC with 1378 bbls gelled fluid.

10/28/02 - Perforate 7610'-7614' (5 holes). Acidize with 1000 gals IC HCL acid.

10/29/02 - Perforate 7396'-7402' (7 holes).

10/30/02 - Acidize 7396'-7402' with 1000 gals IC HCL acid.

10/31/02 - Squeezed perms 7610'-7614' and 7396'-7402' with 350 sx Class "H" cement. Staged in last 6 bbls. Squeezed.

11/6/02 - Cemented to surface with 8 yards redi-mix. Perforate Cherry Canyon 6826'-6846' (21 holes).

11/7/02 - Frac 6826'-6846' with 20# Delta frac 140.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE November 14, 2002

Type or print name Tina L. Huerta

Telephone No. 505-748-1471

(This space for State use)

APPROVED BY

ORIGINAL SIGNED BY TINA L. HUERTA
DISTRICT II SUPERVISOR

Conditions of approval, if any:

NOV 19 2002