

LAND INFORMATION

Distance to Nearest Lease Line

No. Acres in Lease

No. Acres Assigned to Well

Distance to Nearest Well

MUD PROGRAM

Depth	Type	Weight	Remarks
7650-9500'	Fresh Water/Cut Brine	9.1	Starch / LCM for seepage as needed, visc. 29-40
			Flowzan, Barite, BiCarb, Soda Ash, Starch system. Visc. 40
			Chlorides above 90,000 ppm by 8,500'
			Maintain WL of 10 or less below 8800'

TUBULAR PROGRAM

String Type	Hole Size	Depth	Feet	Casing Diameter	Weight	Grade	Connection Type	ERW/ Seamless	Critical Inspectn
Liner	6-1/8"	9500	2700	4-1/2"	11.5	L-80	LTC	ERW	Dnft

Note: Pipe to end up in hole from top to bottom as shown.

CEMENT PROGRAM

String Type	DV Depth	Stage Lead/Tail	Cement Bottom	Cement Top	No Sacks	Cement Type	Cement Yield	Cement Weight
Liner		All	9500	6800	520	50/50 Poz	1.35	14.2
							(175% Excess)	

BOP PROGRAM

Hole Size	Exhibit	Pressure Rating
6-1/8"		3M

Remarks: Install H2S equipment throughout operations. Cisco is Sour

Mud Logger from drill out to TD

Prepared By:

B. D. Schaneman

Date: 11/20/2002