

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
2040 Pacheco St.  
Santa Fe, NM 87505

WELL API NO.  
30-015-32061

Indicate Type of Lease  
STATE ☒ FEE ☐

State Oil & Gas Lease No.  
V 232-1

Lease Name or Unit Agreement Name  
Esperanza 23 State Com

Well No.  
1

Pool name or Wildcat  
Burton Flats Morrow

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

Type of Well:  
OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator  
Mewbourne Oil Company

Address of Operator  
PO Box 5270, Hobbs, New Mexico

Well Location  
Unit Letter F : 2500 Feet From The North Line and 1700 Feet From The West Line  
Section 23 Township 21S Range 27E NMPM Eddy County

Elevation (Show whether DF, RKB, RT, GR, etc.)  
3239

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☐  
CASING TEST AND CEMENT JOB ☒  
OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11/24/01...MI & spud 17 1/2" hole @ 10:00 am.  
11/25/01...TD'ed 17 1/2" hole @ 401'. Ran 401' 13 3/8" H-40 ST/C csg. Cemented w/ 200 sks BJ Lite 'C' w/ additives. Mixed @ 12.4 #/g w/ 2.01cf/sk yd. Tailed w/ 200 sks 'C' w/ 2% CaCl<sub>2</sub>. Mixed @ 14.8 #/g w/ 1.34 cf/sk yd. Circl 78 sks to pit. WOC 18 hrs. Tested BOP to 1000 psi. Drill out w/ 12 1/4" bit.  
11/28/01...TD'ed 12 1/4" hole @ 2605'. Ran 2605' 8 5/8" J-55 ST/C csg. Cemented w/ 750 sks BJ Lite 'C' w/ additives. Mixed @ 12.4 #/g w/ 2.09cf/sk yd. Tailed w/ 200 sks 'C' w/ 2% CaCl<sub>2</sub>. Mixed @ 14.8 #/g w/ 1.34 cf/sk yd. Circl 100 sks to pit. WOC 18 hrs. Tested BOP & Equipment to 2500 psi. Drill out w/ 7 7/8" bit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE District Manager

DATE 11-29-01

TYPE OR PRINT NAME N.M. Young

TELEPHONE NO. 505-393-5905

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM  
DISTRICT II SUPERVISOR

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

DEC 10 2001