

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

## OIL CONSERVATION DIVISION

2040 Pacheco St.  
Santa Fe, NM 87505

*CISF*

WELL API NO. 30-015-32111
Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
State Oil & Gas Lease No. VB 551
Lease Name or Unit Agreement Name Liberty 36 State Com
Well No. 1
Pool name or Wildcat Burton Flats Morrow

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	
Name of Operator Mewbourne Oil Company	Well No. 1
Address of Operator PO Box 5270, Hobbs, NM 88241	Pool name or Wildcat Burton Flats Morrow
Well Location Unit Letter <u>A</u> : <u>660</u> Feet From The <u>North</u> Line and <u>990</u> Feet From The <u>East</u> Line Section <u>36</u> Township <u>20 S</u> Range <u>28E</u> NMPM <u>Eddy</u> County	
Elevation (Show whether DF, RKB, RT, GR, etc.) 3230' GL	

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

### SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☒  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12/28/01...MI Spud 17 1/2" Hole.

12/29/01...TD'ed 17 1/2" hole @ 525'. Ran 525' 13 3/8" H-40 48# ST/C csg. Cemented w/ 265 sks BJ Lite w/ additives Mixed @ 12.5 #/g & 1.98 cf/sk yd. Tailed w/ 200 sks 'C' w/ 2% CaCl<sub>2</sub>. Mixed @ 14.8 #/g & 1.34 yd. Circ 70 sks to surface. WOC 18 hrs. Test BOP equipment to 600 psi. OK. Drill out w/ 12 1/4" Bit.

1/05/02...Drilled to 1685'. Had lost circ & hole problems. Start P&A of well.

1/08/02...P&A'ed Liberty 36 State Com #1 @ 4:00 am. 1/8/02. Install DHM & Release Rig. Will skid rig to Liberty 36 State Com #1-Y located @ 660' FNL & 1300' FEL Sec 36 T-20S R-28E. New C-101 Attached. Plugging Report attached.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE *N.M. Young* TITLE District Manager DATE 01-10-02

TYPE OR PRINT NAME N.M. Young TELEPHONE NO. 505-393-5905

(This space for State Use)

APPROVED BY

CONDITIONS OF APPROVAL, IF

FOR RECORD ONLY

DATE

**JAN 10 2002**

## Liberty "36" State Com #1

01/10/2002

- 1<sup>st</sup> Plug @ 1623' w/200 sks Class C w/2% CaCl<sub>2</sub>. WOC. RIH & tag @ 1640'.
- 2<sup>nd</sup> Plug @ 1623' w/100 sks Class C w/3% CaCl<sub>2</sub>. WOC. RIH & tag @ 1640'.
- 3<sup>rd</sup> Plug @ 1623' w/100 sks Class C w/3% CaCl<sub>2</sub>. WOC. RIH & tag @ 1636'.
- 4<sup>th</sup> Plug @ 1623' w/50 sks Class "C" w/3% CaCl<sub>2</sub>. WOC. Tag @ 1636'.
- 5<sup>th</sup> Plug @ 1623' w/50 sks Class "C" w/3% CaCl<sub>2</sub>. WOC. Tag @ 1636'.
- 6<sup>th</sup> Plug @ 1623' w/25 sks Class "C" w/3% CaCl<sub>2</sub>. WOC. Tag @ 1636'.
- 7<sup>th</sup> Plug @ 1623' w/50 sks Class "C" w/3% CaCl<sub>2</sub>. WOC. Tag @ 1636'.
- 8<sup>th</sup> Plug @ 1623' w/50 sks Class "C" w/3% CaCl<sub>2</sub>. WOC. Tag @ 1636'.
- 9<sup>th</sup> Plug @ 1623' w/65 sks Class "C" w/3% CaCl<sub>2</sub>. WOC. Tag @ 1636'.
- 10<sup>th</sup> Plug @ 1623' w/100 sks Class "C" w/5% CaCl<sub>2</sub>. WOC. Tag @ 1632'.
- 11<sup>th</sup> Plug @ 1592' w/90 sks Thixad w/1% CaCl<sub>2</sub>. WOC. Tag @ 1626'.
- 12<sup>th</sup> Plug @ 1592' w/90 sks Thixad w/1% CaCl<sub>2</sub>. WOC. Tag @ 1626'.
- 13<sup>th</sup> Plug @ 1592' w/75 sks Class "C" w/3% CaCl<sub>2</sub>. WOC. Tag @ 1620'.
- 14<sup>th</sup> Plug @ 1592' w/100 sks Thixad Tropic w/2% CaCl<sub>2</sub>. WOC. Tag @ 1359'.
- 15<sup>th</sup> Plug @ 1313' w/50 sks Class "C" w/3% CaCl<sub>2</sub>. WOC. Tag @ 1301'. Circulate
- 16<sup>th</sup> Plug @ 1065'-951' w/50 sks Class "C". WOC. Tag not required.
- 17<sup>th</sup> Plug @ 575' w/50 sks Thixad Tropic w/2% CaCl<sub>2</sub>. WOC. Tag. Not there.
- 18<sup>th</sup> Plug @ 575' w/50 sks Class "C" w/3% CaCl<sub>2</sub>. WOC. Tag. Not there.
- 19<sup>th</sup> Plug @ 575' w/50 sks Class "C" w/5% CaCl<sub>2</sub>. WOC. Tag. Not there.
- 20<sup>th</sup> Plug @ 575' w/50 sks Class "C" w/5% CaCl<sub>2</sub>. WOC. Tag. Not there.
- Set Howco CIBP @ 85'.
- 21<sup>st</sup> Plug @ 85' w/25 sks Class "C" w/2% CaCl<sub>2</sub>. Circulated 5 sks to surface.