

Measured Depth	Inclin. Degrees	Azimuth Degrees	True Vert Depth	R E C T A N G U L A R C O O R D I N A T E S		Dogleg Deg/100ft	Vert Sect	
7832.00	18.70	38.30	7666.78	980.88 N	841.50 E	0.32	1292.30	
7896.00	17.10	37.60	7727.68	996.39 N	853.60 E	2.52	1311.96	
7960.00	16.90	37.60	7788.88	1011.21 N	865.01 E	0.31	1330.66	
8023.00	16.40	38.00	7849.24	1025.47 N	876.08 E	0.81	1348.69	
8086.00	16.40	37.30	7909.68	1039.56 N	886.94 E	0.31	1366.47	
8200.00	15.48	39.42	8019.29	1064.11 N	906.36 E	0.95	1397.75	GYRO SURVEY POINT
8300.00	14.10	41.18	8115.98	1083.59 N	922.85 E	1.45	1423.28	GYRO SURVEY POINT
8452.00	10.75	41.00	8264.40	1108.23 N	944.35 E	2.20	1455.97	S/S SURVEY POINT
8514.00	9.50	41.00	8325.43	1116.46 N	951.50 E	2.02	1466.87	S/S SURVEY POINT
8576.00	8.80	45.60	8386.64	1123.64 N	958.24 E	1.63	1476.71	
8606.00	8.50	45.00	8416.30	1126.81 N	961.45 E	1.04	1481.20	
8668.00	9.30	41.00	8477.55	1133.83 N	967.98 E	1.63	1490.77	
8729.00	9.40	39.70	8537.74	1141.38 N	974.39 E	0.38	1500.68	
8787.00	8.80	39.90	8595.01	1148.43 N	980.26 E	1.04	1509.86	
8846.00	9.20	39.70	8653.29	1155.52 N	986.17 E	0.68	1519.09	
8907.00	8.80	39.50	8713.54	1162.88 N	992.25 E	0.66	1528.63	
8969.00	9.70	39.20	8774.73	1170.58 N	998.57 E	1.45	1538.59	
9030.00	9.40	40.30	8834.88	1178.36 N	1005.04 E	0.58	1548.71	
9062.00	8.90	39.90	8866.48	1182.26 N	1008.32 E	1.58	1553.80	
9126.00	9.10	39.00	8929.69	1189.99 N	1014.68 E	0.38	1563.81	
9190.00	10.00	38.00	8992.80	1198.30 N	1021.29 E	1.43	1574.43	
9254.00	10.10	39.00	9055.82	1207.04 N	1028.24 E	0.31	1585.59	
9317.00	9.80	42.10	9117.87	1215.31 N	1035.31 E	0.97	1596.47	
9381.00	9.70	42.30	9180.95	1223.34 N	1042.59 E	0.16	1607.30	
9444.00	9.50	43.80	9243.07	1231.02 N	1049.76 E	0.51	1617.79	
9507.00	9.00	44.30	9305.25	1238.30 N	1056.80 E	0.80	1627.89	
9571.00	9.50	42.50	9368.41	1245.77 N	1063.87 E	0.90	1638.16	
9635.00	9.60	45.40	9431.53	1253.42 N	1071.23 E	0.77	1648.75	
9700.00	8.90	48.90	9495.68	1260.53 N	1078.88 E	1.38	1659.12	
9764.00	9.30	47.90	9558.88	1267.25 N	1086.45 E	0.67	1669.13	
9827.00	8.10	52.20	9621.15	1273.38 N	1093.73 E	2.17	1678.51	
9859.00	7.30	56.90	9652.86	1275.87 N	1097.22 E	3.18	1682.66	
9903.00	7.30	56.90	9696.51	1278.93 N	1101.90 E	0.00	1688.01	

All data is in feet unless otherwise stated.
Coordinates from slot #1 and TVD from rotary table.
Bottom hole distance is 1688.15 on azimuth 40.75 degrees from wellhead.
Vertical section is from N 0.00 W 0.00 on azimuth 40.02 degrees.
Calculation uses the minimum curvature method.
Presented by Baker Hughes INTEQ