

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	CLOSURE		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
8805.00	90.40	179.40	7990.48	-1428.63	-228.57	1439.26	1446.80	189.09	7.27
8837.00	90.40	179.50	7990.26	-1460.63	-228.26	1471.19	1478.36	188.88	31
8869.00	90.70	179.90	7989.95	-1492.62	-228.10	1503.13	1509.95	188.69	1.56
8901.00	90.50	179.00	7989.61	-1524.62	-227.79	1535.06	1541.54	188.50	2.80
8932.00	90.60	177.40	7989.32	-1555.60	-226.81	1565.94	1572.05	188.30	5.17
8964.00	90.90	177.30	7988.90	-1587.57	-225.34	1597.76	1603.48	188.08	.99
8996.00	91.80	177.30	7988.14	-1619.52	-223.83	1629.58	1634.92	187.87	2.81
9028.00	91.40	178.40	7987.25	-1651.49	-222.63	1661.43	1666.42	187.68	3.66
9060.00	90.90	176.20	7986.61	-1683.44	-221.12	1693.25	1697.90	187.48	7.05
9092.00	91.20	178.10	7986.02	-1715.40	-219.53	1725.06	1729.39	187.29	6.01
9124.00	90.80	178.40	7985.46	-1747.38	-218.55	1756.94	1760.99	187.13	1.56
9156.00	89.80	178.50	7985.29	-1779.36	-217.69	1788.82	1792.63	186.97	3.14
9188.00	89.90	178.00	7985.38	-1811.35	-216.71	1820.70	1824.27	186.82	1.59
9219.00	90.30	178.10	7985.32	-1842.33	-215.66	1851.57	1854.91	186.68	1.33
9251.00	90.30	178.00	7985.16	-1874.31	-214.57	1883.44	1886.55	186.53	31
9283.00	89.80	177.50	7985.13	-1906.29	-213.31	1915.30	1918.18	186.38	2.21
9315.00	89.10	177.20	7985.44	-1938.25	-211.83	1947.12	1949.79	186.24	2.38
9347.00	88.60	178.40	7986.08	-1970.22	-210.60	1978.97	1981.44	186.10	4.06
9379.00	88.70	177.20	7986.83	-2002.19	-209.37	2010.82	2013.10	185.97	3.76
9411.00	88.90	178.40	7987.50	-2034.16	-208.15	2042.67	2044.78	185.84	3.80
9442.00	88.90	177.80	7988.10	-2065.13	-207.12	2073.54	2075.49	185.73	1.91
9474.00	89.30	178.60	7988.60	-2097.11	-206.11	2105.41	2107.22	185.61	2.79
9506.00	89.30	178.90	7988.99	-2129.10	-205.42	2137.31	2138.99	185.51	.91
9538.00	88.90	177.90	7989.49	-2161.09	-204.52	2169.19	2170.74	185.41	3.37
9569.00	88.70	178.40	7990.14	-2192.06	-203.52	2200.06	2201.49	185.30	1.74
9601.00	88.90	177.80	7990.81	-2224.04	-202.46	2231.93	2233.23	185.20	1.98
9633.00	89.00	178.20	7991.40	-2256.01	-201.34	2263.79	2264.98	185.10	1.29
9665.00	89.30	179.50	7991.87	-2288.00	-200.70	2295.69	2296.79	185.01	4.17
9697.00	89.60	179.00	7992.18	-2320.00	-200.28	2327.61	2328.63	184.93	1.82
9760.00	90.00	177.80	7992.40	-2382.97	-198.52	2390.38	2391.23	184.76	2.01
9813.00	90.30	177.50	7992.26	-2435.93	-196.35	2443.13	2443.83	184.61	80
-- Projection to Bit--									
9850.00	90.30	177.50	7992.07	-2472.89	-194.74	2479.94	2480.55	184.50	00