ORM 3160-5	UNIT	STATES	FORM APPROVED
June 1990)		OF THE INTERIOR	Budget Bureau No. 1004-0135
	BUREAU OF LA	ND MANAGEMENT	Expires: March 31, 1993
			5. Lease Designation and Serial No.
	SUNDRY NOTICES AND	REPORTS ON WELLS	NM-0560289
Do not use this form for proposals to drill or		r to deepen or reenter a different reservoir.	6. If Indian, Allottee or Tribe Name
	Use "APPLICATION FOR PE	ERMIT -" for such proposals	
			7. If Unit or CA, Agreement Designation
		COLORATE 2456789702	
	SUBMITINT	TRIPLICATE	Burton Flat Deep Unit
I. Type of Well		CAR TO	8. Well Name and No.
Oi⊧ Well	X Gas Well Other	type other description or gelete	Burton Flat Deep Unit #44
		121	9. API Well No.
2. Name of Ope	erator /		30-015-32274
	Ocean Energy Inc.	Separation 1	10. Field and Pool, or Exploratory Area
Address and	Telephone No.		Burton Flat Deep (Wildcat-Devonia
	nnin, Suite 1600, Houston, TX	77002 (713) 265-6834	11. County or Parish, State
	Vell (Footage, Sec., T., R., M., or Surv		
	SL & 1660' FWL, Sec. 3, Lot 14		Eddy Co., NM
55557 6	je a 1000 i We, 000. 0, 200 i	,, , , , , , , , , , , , , , , , , , ,	
12		BOX(05) TO INDICATE NATURE OF NOTICE	
12.		BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	
I Y I	PE OF SUBMISSION		JF ACTION
	Notice of Intent	Abandonment	Change of Plans
		Recompletion	New Construction
	X Subsequent Report	Plugging Back	Non-Routine Fracturing
		Casing Repair	Water Shut-Off
Final Abandonment Notice		Altering Casing	Conversion to Injection
		X Other Spud & Casing setting	Dispose Water
		(Note: Report results of multiple comp	Letion on Well
		Completion or Recompletion Report a	nd Log form.)
13. Describe Pr	roposed or Completed Operations (Cl	early state all pertinent details, and give pertinent dat	
			or all markers and zones pertinent to this work.)*
WORK. II WE	Il is directionally drilled dive subsuita		
	ell is directionally drilled, give subsuffa	de locations and measured and true vertical depuis i	
6/1/02			
6/1/02	Spud well w/GW Rig #33 @ 1	1900 hrs. 20" conductor set @ 40'.	
6/2/02	Spud well w/GW Rig #33 @ 1 Drill to 620'. Prep to run surfa	1900 hrs. 20" conductor set @ 40'. ace casing.	
	Spud well w/GW Rig #33 @ 1 Drill to 620'. Prep to run surfa Depth 620'. Ran 48 jts 13-3/8	1900 hrs. 20" conductor set @ 40'. ace casing. 3" H-40 ST&C casing, set @ 620'. Cement	ted w/300 sxs 50/50 Poz_plus additives.
6/2/02 6/3/02 to	Spud well w/GW Rig #33 @ 1 Drill to 620'. Prep to run surfa Depth 620'. Ran 48 jts 13-3/8 Tail w/200 sx Cl C + 2% CaCl2,	1900 hrs. 20" conductor set @ 40'. ace casing. 8" H-40 ST&C casing, set @ 620'. Cement wt 14.8 ppm. Good circ through out entire job,	ted w/300 sxs 50/50 Poz_plus additives.
6/2/02 6/3/02	Spud well w/GW Rig #33 @ 1 Drill to 620'. Prep to run surfa Depth 620'. Ran 48 jts 13-3/8 Tail w/200 sx CI C + 2% CaCl2, Test 13-3/8" csg to 500 psi. Dril	1900 hrs. 20" conductor set @ 40'. ace casing. 8" H-40 ST&C casing, set @ 620'. Cement wt 14.8 ppm. Good circ through out entire job, Il cmt, shoe and formation.	ed w/300 sxs 50/50 Poz plus additives. acirc 102 sx cmt. WOC 18-1/2 hrs. Test
6/2/02 6/3/02 to	Spud well w/GW Rig #33 @ 1 Drill to 620'. Prep to run surfa Depth 620'. Ran 48 jts 13-3/8 Tail w/200 sx CI C + 2% CaCl2, Test 13-3/8" csg to 500 psi. Dril Drill and survey to 2810'. Ran 6	1900 hrs. 20" conductor set @ 40'. ace casing. 8" H-40 ST&C casing, set @ 620'. Cement wt 14.8 ppm. Good circ through out entire job, Il cmt, shoe and formation. 3 jts 9-5/8" J-55 30# LT&C set @ 2810'. Cmtd	ted w/300 sxs 50/50 Poz plus additives. acirc 102 sx cmt. WOC 18-1/2 hrs. Test w/120 sx cmt - lead - Cl H + additives.
6/2/02 6/3/02 to 6/4/02 6/5/02 to	Spud well w/GW Rig #33 @ 1 Drill to 620'. Prep to run surfa Depth 620'. Ran 48 jts 13-3/8 Tail w/200 sx CI C + 2% CaCl2, Test 13-3/8" csg to 500 psi. Dril Drill and survey to 2810'. Ran 6 2nd lead - 900 sx 50/50 POZ CI	1900 hrs. 20" conductor set @ 40'. ace casing. 8" H-40 ST&C casing, set @ 620'. Cement wt 14.8 ppm. Good circ through out entire job, Il cmt, shoe and formation. 3 jts 9-5/8" J-55 30# LT&C set @ 2810'. Cmtd H + additives. Tail w/CI C + additives, 185 sx t	ted w/300 sxs 50/50 Poz plus additives. acirc 102 sx cmt. WOC 18-1/2 hrs. Test w/120 sx cmt - lead - Cl H + additives. to surface, full circulation, bumped plug to
6/2/02 6/3/02 to 6/4/02 6/5/02 to	Spud well w/GW Rig #33 @ 1 Drill to 620'. Prep to run surfa Depth 620'. Ran 48 jts 13-3/8 Tail w/200 sx CI C + 2% CaCl2, Test 13-3/8" csg to 500 psi. Dril Drill and survey to 2810'. Ran 6 2nd lead - 900 sx 50/50 POZ CI	1900 hrs. 20" conductor set @ 40'. ace casing. 8" H-40 ST&C casing, set @ 620'. Cement wt 14.8 ppm. Good circ through out entire job, Il cmt, shoe and formation. 3 jts 9-5/8" J-55 30# LT&C set @ 2810'. Cmtd	ted w/300 sxs 50/50 Poz plus additives. acirc 102 sx cmt. WOC 18-1/2 hrs. Test w/120 sx cmt - lead - Cl H + additives. to surface, full circulation, bumped plug to
6/2/02 6/3/02 to 6/4/02 6/5/02 to 6/10/02	Spud well w/GW Rig #33 @ 1 Drill to 620'. Prep to run surfa Depth 620'. Ran 48 jts 13-3/8 Tail w/200 sx CI C + 2% CaCl2, Test 13-3/8" csg to 500 psi. Dril Drill and survey to 2810'. Ran 6 2nd lead - 900 sx 50/50 POZ CI 1650 psi - floats held. WOC 23 to 7/8/02 Drill and survey to 126	1900 hrs. 20" conductor set @ 40'. ace casing. 3" H-40 ST&C casing, set @ 620'. Cement wt 14.8 ppm. Good circ through out entire job, Il cmt, shoe and formation. 3 jts 9-5/8" J-55 30# LT&C set @ 2810'. Cmtd H + additives. Tail w/CI C + additives, 185 sx t hrs. Test BOP's 5000# high, 500# low. Test 9 500'.	ed w/300 sxs 50/50 Poz plus additives. acirc 102 sx cmt. WOC 18-1/2 hrs. Test w/120 sx cmt - lead - Cl H + additives. to surface, full circulation, bumped plug to -5/8" csg to 1500 psi - good.
6/2/02 6/3/02 to 6/4/02 6/5/02 to 6/10/02	Spud well w/GW Rig #33 @ 1 Drill to 620'. Prep to run surfa Depth 620'. Ran 48 jts 13-3/8 Tail w/200 sx CI C + 2% CaCl2, Test 13-3/8" csg to 500 psi. Dril Drill and survey to 2810'. Ran 6 2nd lead - 900 sx 50/50 POZ CI 1650 psi - floats held. WOC 23 to 7/8/02 Drill and survey to 126	1900 hrs. 20" conductor set @ 40'. ace casing. 8" H-40 ST&C casing, set @ 620'. Cement wt 14.8 ppm. Good circ through out entire job, Il cmt, shoe and formation. 13 jts 9-5/8" J-55 30# LT&C set @ 2810'. Cmtd H + additives. Tail w/CI C + additives, 185 sx t hrs. Test BOP's 5000# high, 500# low. Test 9	ed w/300 sxs 50/50 Poz plus additives. acirc 102 sx cmt. WOC 18-1/2 hrs. Test w/120 sx cmt - lead - Cl H + additives. to surface, full circulation, bumped plug to -5/8" csg to 1500 psi - good.
6/2/02 6/3/02 to 6/4/02 6/5/02 to 6/10/02	Spud well w/GW Rig #33 @ 1 Drill to 620'. Prep to run surfa Depth 620'. Ran 48 jts 13-3/8 Tail w/200 sx CI C + 2% CaCl2, Test 13-3/8" csg to 500 psi. Dril Drill and survey to 2810'. Ran 6 2nd lead - 900 sx 50/50 POZ CI 1650 psi - floats held. WOC 23 to 7/8/02 Drill and survey to 126 Ran 285 jts of 7" csg & set @ 12	1900 hrs. 20" conductor set @ 40'. ace casing. 3" H-40 ST&C casing, set @ 620'. Cement wt 14.8 ppm. Good circ through out entire job, Il cmt, shoe and formation. 3 jts 9-5/8" J-55 30# LT&C set @ 2810'. Cmtd H + additives. Tail w/CI C + additives, 185 sx t hrs. Test BOP's 5000# high, 500# low. Test 9 500'.	ed w/300 sxs 50/50 Poz plus additives. acirc 102 sx cmt. WOC 18-1/2 hrs. Test w/120 sx cmt - lead - Cl H + additives. to surface, full circulation, bumped plug to -5/8" csg to 1500 psi - good.
6/2/02 6/3/02 to 6/4/02 6/5/02 to 6/10/02	Spud well w/GW Rig #33 @ 1 Drill to 620'. Prep to run surfa Depth 620'. Ran 48 jts 13-3/8 Tail w/200 sx CI C + 2% CaCl2, Test 13-3/8" csg to 500 psi. Dril Drill and survey to 2810'. Ran 6 2nd lead - 900 sx 50/50 POZ CI 1650 psi - floats held. WOC 23 to 7/8/02 Drill and survey to 126 Ran 285 jts of 7" csg & set @ 12	1900 hrs. 20" conductor set @ 40'. ace casing. 8" H-40 ST&C casing, set @ 620'. Cement wt 14.8 ppm. Good circ through out entire job, Il cmt, shoe and formation. 3 jts 9-5/8" J-55 30# LT&C set @ 2810'. Cmtd H + additives. Tail w/CI C + additives, 185 sx t hrs. Test BOP's 5000# high, 500# low. Test 9 500'. 2,600'. Cmtd w/640 sk Poz H & C. Bumped pl	ed w/300 sxs 50/50 Poz plus additives. acirc 102 sx cmt. WOC 18-1/2 hrs. Test w/120 sx cmt - lead - Cl H + additives. to surface, full circulation, bumped plug to -5/8" csg to 1500 psi - good.
6/2/02 6/3/02 to 6/4/02 6/5/02 to 6/10/02 6-11-02	Spud well w/GW Rig #33 @ 1 Drill to 620'. Prep to run surfa Depth 620'. Ran 48 jts 13-3/8 Tail w/200 sx CI C + 2% CaCl2, Test 13-3/8" csg to 500 psi. Dril Drill and survey to 2810'. Ran 6 2nd lead - 900 sx 50/50 POZ CI 1650 psi - floats held. WOC 23 to 7/8/02 Drill and survey to 126 Ran 285 jts of 7" csg & set @ 12 cementing. TOC 9500'. Set slip	1900 hrs. 20" conductor set @ 40'. ace casing. 8" H-40 ST&C casing, set @ 620'. Cement wt 14.8 ppm. Good circ through out entire job, Il cmt, shoe and formation. 13 jts 9-5/8" J-55 30# LT&C set @ 2810'. Cmtd H + additives. Tail w/CI C + additives, 185 sx t hrs. Test BOP's 5000# high, 500# low. Test 9 500'. 2,600'. Cmtd w/640 sk Poz H & C. Bumped pl os, install wellhead, test. Rig released 7/8/02.	ed w/300 sxs 50/50 Poz plus additives. acirc 102 sx cmt. WOC 18-1/2 hrs. Test w/120 sx cmt - lead - Cl H + additives. to surface, full circulation, bumped plug to -5/8" csg to 1500 psi - good.
6/2/02 6/3/02 to 6/4/02 6/5/02 to 6/10/02 6-11-02	Spud well w/GW Rig #33 @ 1 Drill to 620'. Prep to run surfa Depth 620'. Ran 48 jts 13-3/8 Tail w/200 sx CI C + 2% CaCl2, Test 13-3/8" csg to 500 psi. Dril Drill and survey to 2810'. Ran 6 2nd lead - 900 sx 50/50 POZ CI 1650 psi - floats held. WOC 23 to 7/8/02 Drill and survey to 126 Ran 285 jts of 7" csg & set @ 12 cementing. TOC 9500'. Set slip	1900 hrs. 20" conductor set @ 40'. ace casing. 8" H-40 ST&C casing, set @ 620'. Cement wt 14.8 ppm. Good circ through out entire job, Il cmt, shoe and formation. 3 jts 9-5/8" J-55 30# LT&C set @ 2810'. Cmtd H + additives. Tail w/CI C + additives, 185 sx f hrs. Test BOP's 5000# high, 500# low. Test 9 500'. 2,600'. Cmtd w/640 sk Poz H & C. Bumped pl os, install wellhead, test. Rig released 7/8/02.	ed w/300 sxs 50/50 Poz plus additives. acirc 102 sx cmt. WOC 18-1/2 hrs. Test w/120 sx cmt - lead - CI H + additives. to surface, full circulation, bumped plug to -5/8" csg to 1500 psi - good. lug, floats held. Full circulation during
6/2/02 6/3/02 to 6/4/02 6/5/02 to 6/10/02 6-11-02	Spud well w/GW Rig #33 @ 1 Drill to 620'. Prep to run surfa Depth 620'. Ran 48 jts 13-3/8 Tail w/200 sx CI C + 2% CaCl2, Test 13-3/8" csg to 500 psi. Dril Drill and survey to 2810'. Ran 6 2nd lead - 900 sx 50/50 POZ CI 1650 psi - floats held. WOC 23 to 7/8/02 Drill and survey to 126 Ran 285 jts of 7" csg & set @ 12 cementing. TOC 9500'. Set slip certify that the foregoing is true ar	1900 hrs. 20" conductor set @ 40'. ace casing. 8" H-40 ST&C casing, set @ 620'. Cement wt 14.8 ppm. Good circ through out entire job, Il cmt, shoe and formation. 13 jts 9-5/8" J-55 30# LT&C set @ 2810'. Cmtd H + additives. Tail w/CI C + additives, 185 sx t hrs. Test BOP's 5000# high, 500# low. Test 9 500'. 2,600'. Cmtd w/640 sk Poz H & C. Bumped pl os, install wellhead, test. Rig released 7/8/02.	ed w/300 sxs 50/50 Poz plus additives. acirc 102 sx cmt. WOC 18-1/2 hrs. Test w/120 sx cmt - lead - CI H + additives. to surface, full circulation, bumped plug to -5/8" csg to 1500 psi - good. lug, floats held. Full circulation during
6/2/02 6/3/02 to 6/4/02 6/5/02 to 6/10/02 6-11-02	Spud well w/GW Rig #33 @ 1 Drill to 620'. Prep to run surfa Depth 620'. Ran 48 jts 13-3/8 Tail w/200 sx CI C + 2% CaCl2, Test 13-3/8" csg to 500 psi. Dril Drill and survey to 2810'. Ran 6 2nd lead - 900 sx 50/50 POZ CI 1650 psi - floats held. WOC 23 to 7/8/02 Drill and survey to 126 Ran 285 jts of 7" csg & set @ 12 cementing. TOC 9500'. Set slip	1900 hrs. 20" conductor set @ 40'. ace casing. 8" H-40 ST&C casing, set @ 620'. Cement wt 14.8 ppm. Good circ through out entire job, Il cmt, shoe and formation. 3 jts 9-5/8" J-55 30# LT&C set @ 2810'. Cmtd H + additives. Tail w/CI C + additives, 185 sx f hrs. Test BOP's 5000# high, 500# low. Test 9 500'. 2,600'. Cmtd w/640 sk Poz H & C. Bumped pl os, install wellhead, test. Rig released 7/8/02.	ted w/300 sxs 50/50 Poz plus additives. acirc 102 sx cmt. WOC 18-1/2 hrs. Test w/120 sx cmt - lead - Cl H + additives. to surface, full circulation, bumped plug to -5/8" csg to 1500 psi - good. ug, floats held. Full circulation during
6/2/02 6/3/02 to 6/4/02 6/5/02 to 6/10/02 6-11-02	Spud well w/GW Rig #33 @ 1 Drill to 620'. Prep to run surfa Depth 620'. Ran 48 jts 13-3/8 Tail w/200 sx CI C + 2% CaCl2, Test 13-3/8" csg to 500 psi. Dril Drill and survey to 2810'. Ran 6 2nd lead - 900 sx 50/50 POZ CI 1650 psi - floats held. WOC 23 to 7/8/02 Drill and survey to 126 Ran 285 jts of 7" csg & set @ 12 cementing. TOC 9500'. Set slip certify that the foregoing is true ar	1900 hrs. 20" conductor set @ 40'. ace casing. 8" H-40 ST&C casing, set @ 620'. Cement wt 14.8 ppm. Good circ through out entire job, Il cmt, shoe and formation. 3 jts 9-5/8" J-55 30# LT&C set @ 2810'. Cmtd H + additives. Tail w/CI C + additives, 185 sx f hrs. Test BOP's 5000# high, 500# low. Test 9 500'. 2,600'. Cmtd w/640 sk Poz H & C. Bumped pl os, install wellhead, test. Rig released 7/8/02.	ed w/300 sxs 50/50 Poz plus additives. acirc 102 sx cmt. WOC 18-1/2 hrs. Test w/120 sx cmt - lead - CI H + additives. to surface, full circulation, bumped plug to -5/8" csg to 1500 psi - good. lug, floats held. Full circulation during

representations as to any matter within its jurisdiction.