Do not u abandor	UNI STAT DEPARTMEN. JF THI BUREAU OF LAND MAI NDRY NOTICES AND REF use this form for proposals and well. Use Form 3160-3 (A	E INTERIOR NAGEMENT PORTS ON WELLS to drill or to re-enter an APD) for such proposals	1301 W. Artesia	Grand, ,NMMM8	FORM APPROVED DEXP Solvember 30, 2000 AVENUE 8210 Allottee or Tribe Name
SUBMIT IN	N TRIPLICATE - Other ins	tructions on reverse	ida 23456	7. If Unit or	CA/Agreement, Name and/or No.
Type of Well     Oil Well Gas W     Name of Operator	/ell 🖾 Other	Wally Frank	2002	8 Well Name and No. Jones Canyon "4" Federal #7	
Devon-SFS Operating, Inc. / a. Address 20 N. Broadway, Ste 1500, OKC, OK 73102		Senior Operat 3b. Phone No Enclud (405)552-4595	ions Engr.	<ul> <li>9. API Well No.</li> <li>30-015-32293</li> <li>10. Field and Pool, or Exploratory Area</li> </ul>	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) SHL: 1750' FNL & 990' FEL, Unit H, Section 4-T22S-R24E, Eddy Cny, 1 BHL: 711' FNL & 684' FEL, Unit A, Section 4-T22S-R24E, Eddy Cnty, N			ŇМ	Eddy Cnty, New Mexico	
12. CHEC TYPE OF SUBMISSIO	K APPROPRIATE BOX(ES)			EPORT, OR	OTHER DATA
<ul> <li>Notice of Intent</li> <li>Subsequent Report</li> </ul>	Acidize     Alter Casing     Casing Repair     Change Plans	Deepen Fracture Treat New Construction Plug and Abandon	PE OF ACTION  Production (Start Reclamation  Recomplete Temporarily Aba	,	<ul> <li>□ Water Shut-Off</li> <li>□ Well Integrity</li> <li>□ Other Spud, casing strings,</li> </ul>
Final Abandonment No     Final Abandonment No     If the proposed or Co     If the proposal is to deep	tice Convert to Injection	Plug Back	Water Disposal	v proposed wo	WOCU
Attach the Bond under w following completion of testing has been complete	which the work will be performed or p the involved operations. If the operat ed. Final Abandonment Notices shal s ready for final inspection.)	provide the Bond No. on file wi tion results in a multiple complete	th BLM/BIA. Required tion or recompletion in	subsequent rep a new interval.	ports shall be filed within 30 days a Form 3160-4 shall be filed once

1

NOTE: Revised proposed BHL after drlg from 660' FNL & 660' FWL to actual BHL at 711' FNL & 684' FEL of Section 4-T22S-R24E in Eddy Cnty, New Mexico.

6-1-2002 thru 7-7-2002 Spud 12 1/4" hole at 1400 hrs on 5-31-2002. Air drld to 1303'; had trouble with the hole sloughing due to large rocks. Set 100 sx cement plug with bottom of DP at 1278'. Drld cement 1240-1303'. Drld new hole to 1313'. Had to free DP. POH and LDDP. Rigged down and moved out United Drlg. Moved in and rigged up Patterson-UTI Drlg.

On 6-27-2002 resumed drlg operations. Washed, reamed, worked DP to 1291'. Set 200 sx Class C plug at 1291'. Drld cement 1257-1291'. Washed and reamed to 1323'. Air drld new hole to 1815'.

On 6-14-2002 ran 40 jts 9 5/8" 36# J-55 ST&C casing, set at 1815'; cemented with 700 sx Class C. Ran Temp svy and found TOC at 1086'. Topped with 475 sx Class C; TOC at surface. WOC 20 hrs. (Continued on the reverse.)

		ACCEPTED FOR RECORD
14. Thereby certify that the foregoing is true and correct Name (Printed/Typed)       Title         Candace R. Graham 405/235-3611 X4520       Engineering		AUG :: Ü 2002
Candace R. Fraham	Date 08/20/2002	ALEXIS C. SWOBODA
THIS SPACE FO	R FEDERAL OR STATE OFFICE	
Approved by	Title	Date
Conditions of approval, if any, are attached. Approval of this notice of certify that the applicant holds legal or equitable title to those rights in which would entitle the applicant to conduct operations thereon.		I
Title 18 U.S.C. Section 1001 makes it a prime for any sector have been		

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on reverse)

Devon-SFS Operating, Inc. PPI 30-015-32293 BLM Lease Serial No. NM-NM83037 JOUES CANYON "4" FEDERAL #7 SHL: 1750' FNL & 684' FEL, Unit H, Section 4-T22S-R24E BHL: 711' FNL & 684' FEL, Unit A, Section 4-T22S-R24E Eddy Cnty, NM Drilling Sundry 3160-5 Page 2 Page 2

6-1-2002 thru 7-7-2002 (Continued from the front.)

Drld 8 3/4" hole. Reached kick-off point at 3500' on 6-18-2002. Reached TD 8871', TVD 8669', at 0800 hrs on 7-2-2002. Schlumberger ran Platform Express Three Detector Litho-Density Compensated Neutron/NGT and Azimuthal Laterolog MCFL/NGT logs on 7-3-2002.

r

Ran 204 jts 7" 23# J-55 & HCL-80 LT&C casing on 7-5-2002; casing set at 8859', DV tools at 3508' and 7957', ESP 8003'; cemented: 1st stage with 150 sx 15/61/11 Class C; 2nd stage with 525 sx 60/40 Pozmix C; TOC surface. Released rig at 1000 hrs 7-6-2002. WOCU.