

District I
1625 W. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

CID
RLM
DP

Form C-101

Revised March 17, 1999

Submit to appropriate District Office
State Lease - 6 Copies
Fee Lease - 5 Copies

SEP 17 1999
RECEIVED
OCD - ARTESIA

AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

¹ Operator Name and Address Ricks Exploration, Inc. 110 W. Louisiana, Suite 410 Midland, TX 79701		² OGRID Number 168489
		³ API Number 30-015-32411
³ Property Code 30564	⁵ Property Name CN Com.	⁶ Well No. 2

⁷ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
P	20	22S	26E		1200	SOUTH	1200	EAST	EDDY

⁸ Proposed Bottom Hole Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from	County

⁹ Proposed Pool 1

Happy Valley, Texas

¹¹ Work Type Code N	¹² Well Type Code G	¹³ Cable/Rotary R	¹⁴ Lease Type Code P	¹⁵ Ground Level Elevation 3323'
¹⁶ Multiple No	¹⁷ Proposed Depth 11,900	¹⁸ Formation MORROW	¹⁹ Contractor N/A	²⁰ Spud Date ASAP

²¹ Proposed Casing and Cement Program

Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
25"	20"	Conductor	40'	Redi-mix	Surface
17-1/2"	13-3/8"	48#	600'	500	Surface
12-1/4"	9-5/8"	40#	2300'	650	Surface
8-3/4"	5-1/2"	17#	11,900'	1050	7000' from surf

²² Describe the proposed program. If this application is to DEEPEN or PLUG BACK, give the data on the present productive zone and proposed new productive zone.

Describe the blowout prevention program, if any. Use additional sheets if necessary.

- Drill 25" hole to 40'. Set 40' of 20" conductor pipe & redi-mix to surface.
- Drill 17-1/2" hole to 600'. Set 600', 13-3/8" 48# H-40 ST&C csg & cmt to surf w/ 500 sx Cl C + additives.
- Drill 12-1/4" hole to +/- 2300'. Run & set 2300' 9-5/8" 40# S-80 & J-55 ST&C csg. Cmt w/ 550 sx of Cl C + additives, tailed w/ 500 sx Cl C cmt + 2% CaCl + additives. Circ cmt to surface.

²³ I hereby certify that the information given above is true and complete to the best of my knowledge and belief.

Signature: *Erick Nelson*

Printed name: Erick Nelson

Title: Operations Engineer

Date:
9/12/02

Phone:
915/ 683-7443

OIL CONSERVATION DIVISION

Approved by: **ORIGINAL SIGNED BY THE O.C.D.
DISTRICT II SUPERVISOR**

Title:
Approval Date: **SEP 27 2002** Expiration Date: **SEP 27 2003**

Conditions of Approval:

Attached ☐

Operator to cover all oil, gas and water bearing zones.

* Was Concho O & G Corp

4. Drill 8-3/4" hole to 11,900'. Set 11,900' of 5-1/2" csg as follows: 1500' of 5-1/2" 17# S-95 LT&C, 7300' of 17# N-80 LT&C, 3100' of 5-1/2" 17# N-80 Buttress. Cmdt w/ 550 sx of Cl H + additives, tailed w/ 500 sx Cl H + additives. Est TOC 7000' from surface.