

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources  
OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103  
Revised March 25, 1999

WELL API NO.	30-015-32411
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
Oil Well ☐ Gas Well ☐ Other ☒

2. Name of Operator  
Ricks Exploration, Inc.

3. Address of Operator  
110 W. Louisiana, Ste 410 Midland, TX 79701

4. Well Location  
Unit Letter P : 1200' feet from the South line and 1200' feet from the East line  
Section 20 Township 22S Range 26E NMPM County Eddy

7. Lease Name or Unit Agreement Name:  
'CN' Com.

8. Well No.  
#2

9. Pool name or Wildcat  
Happy Valley (Morrow)

10. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3323' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☒  
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). \*SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

Ricks Exploration, Inc. respectfully request permission to change the casing design on the above captioned well as follows:

1. Drill 17 1/2" hole to 750'. Set 13 3/8" 48# H-40 casing. Cemented w/300 Light C + additives followed by 200 sxs C + 2% CaCl2. Circ to surface.
2. Drill 12 1/4" hole to 2550'. Set 9 5/8" 40# J-55 casing. Cement w/500 sxs of Light C + additives followed w/200 sxs Cl C + 2% CaCl2. Circ to surface.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Dora Bustamante TITLE Production Analyst DATE 11/14/02

Type or print name Dora Bustamante Telephone No. 915/ 683-7443

(This space for State use)

APPROVED BY Appr TITLE  DATE 11-19-02  
Conditions of approval, if any: