Office	of New Mexico	1.12,	N	Form C-103
istrict I Latergy, Minerals and Natural Resources 625 N. French Dr., Hobbs, NM 88240			L API NO.	Revised March 25, 1999
District II 1301 W. Grand Ave., Artesia, NM 88210 OIL CONSERVATION DIVISION		ISION 5 To	dianta Tuma	30-015-32411
District III 1220 South St. Francis Dr.		r. 3. 11.	5. Indicate Type of Lease STATE FEE	
1000 Rio Brazos Rd., Aztec, NM 87410 District IV Santa Fe, NM 87505		6.	4	
1220 S. St. Francis Dr., Santa Fe, NM				
87505 SUNDRY NOTICES AND REPORTS	ON WELLS	7. L	ease Name or	r Unit Agreement Name:
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A			'CN' Com.	
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)				
1. Type of Well:				
Oil Well Gas Well Other	· · · · · · · · · · · · · · · · · · ·			
2. Name of Operator		′ ≲\ 8. W	ell No.	112
Ricks Exploration, Inc.		2 50 0 0	ool name or V	#2
3. Address of Operator 110 W. Louisiana, Ste 410 Midland, TX 79701	1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	9. Po		/alley (Morrow)
4. Well Location	- 18%	 	тирру у	uncy (Monow)
*	₹.			
Unit Letter P : 1200' feet from t	the <u>South</u>	liñe and <u>1200'</u>	feet from	the <u>East</u> line
Section 20 Township	22S Rai		NMPM	County Eddy
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 3323' GR				
11. Check Appropriate Box to	Indicate Nature	of Notice, Repor	rt or Other	Data
NOTICE OF INTENTION TO:		SUBSEQI	JENT RE	PORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDO	ON 🗌 REM	EDIAL WORK		ALTERING CASING
TEMPORARILY ABANDON	СОМ	MENCE DRILLING	OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING MULTIPLE COMPLETION		CASING TEST AND CEMENT JOB		
OTHER:	ОТН	ER: Spud, Set Sur	f & Intermed	Csg
12. Describe proposed or completed operations. (Clearly	state all pertinent de	etails, and give pert	inent dates, in	ncluding estimated date of
starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.				
11/26/02- Spud 17 ½" hole @ 2:30 am MST.				
11/28/02- Drill 17 ½" hole to 758'. Ran 13 3/8" 48# H-40 ST&C csg & set @ 758'. Cmt csg w/Lead 1: 200 sxs H + additives, Lead 2: 400 sxs 35/65 Poz C + additives & tailed w/200 sxs C + 2% CaCl2. Circ 205 sxs to pit. WOC (18 hrs).				
11/29/02- Weld on head & NU. Test hydrill & csg to 1200 psi- Ok. Resume drlg.				
12/06/02- Drill 12 1/4" hole to 2430'. Ran 9 5/8" 40# J				additives, Lead 2:
600 sxs 50/50/10 4 additivies & tailed w/200 sxs Cl C + 2% CaCl. Circ 175 sxs to pit.				
		Mote we		
I hereby certify that the information above is true and comp	lete to the best of n	ny knowledge and b	elief.	
			01101.	
SIGNATURE Dora Bustamarte	TITLEP	roduction Analyst		DATE12/06/02
	Bustamante		Telephone N	lo. 915/ 683-7443
(This space for State use)				000 . 0 000
APPPROVED BY For No cond on la 13 1	_TITLE		- LA AND DECEMBER	DATE 1 6 2002
Conditions of approval, if any:				