

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.

30-015-32414

Indicate Type of Lease

STATE ☒

FEE ☐

State Oil & Gas Lease No.

K-3633-7

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

Lease Name or Unit Agreement Name

Esperanza 11 State Com

Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

Name of Operator
Mewbourne Oil Company 14744

Well No.

1

Address of Operator
PO Box 5270, Hobbs, NM 88241

Pool name or Wildcat

Burton Flat Morrow

Well Location

Unit Letter M 1010 Feet From The South Line and 660 Feet From The West Line

Section 11 Township 21S Range 27E NMPM Eddy County

Elevation (Show whether DF, RKB, RT, GR, etc.)
3295' GL

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11-13-02...Spud 17 1/2" hole. TD'ed @ 435'. Ran 435' of 13 3/8" 48# H-40 ST/C csg. Cemented w/ 200 sks 65/35/6 'C' Poz w/ additives. Mixed @ 12.4 #/g & 2.01 yd. Tailed w/ 200 sks 'C' w/ 2% CaCl2. Mixed @ 14.8 #/g & 1.34 yd. Circl 14 sks to pit. WOC 18 hrs. Test BOP to 500 psi. OK. Drill out w/ 12 1/4" bit.

11-19-02...TD'ed 12 1/4" hole @ 2608'. Ran 2608' of 8 5/8" 32# J-55 ST/C csg. Cemented w/ 200 sks Thic-Set 'H'. Mixed @ 14.6 #/g & 1.52 yd. 900 sks 65/35/6 'C' Poz w/ additives. Mixed @ 12.4 #/g & 2.09 yd. Tailed w/ 200 sks 'C' w/ 2% CaCl2. Mixed @ 14.8 #/g & 1.34 yd. Circl 100 sks to pit. WOC 18 hrs. Test BOP to 2500 psi. OK. Drilled out w/ 7 7/8" bit. Will test BOP equipment with 3rd party on trip before Wolfcamp.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE District Manager

DATE 11-21-02

TYPE OR PRINT NAME N.M. Young

TELEPHONE NO. 505-393-5905

(This space for State Use)

APPROVED BY

ORIGINAL SIGNED BY THE N. M. MUM
DISTRICT II SUPERVISOR

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

DEC 02 2002