

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Mewbourne Oil Company 14744

3. Address and Telephone No.

PO Box 5270, Hobbs, N.M. 88241. 505-393-5905

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

990' FSL & 1510' FEL Unit Letter O of Sec.25 T-20S R-28E

5. Lease Designation and Serial No.

NM-17103

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Freedom 25 Federal Com #1

9. API Well No.

30-015-32449

10. Field and Pool, or Exploratory Area

Burton Flats Morrow

11. County or Parish, State

Eddy Co., N.M.

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Spud & Csg

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

10-01-02...Spud 26" hole. TD'ed 26" hole @ 406'. Ran 406' 20" 94# H-40 BT&C casing. Cemented w/ 442 sks 65/35 C/Poz w/ 6% gel & additives. Mixed @ 12.4 #/g & 2.01 yd. Tailed w/ 200 sks C w/ 2% CaCl2. Mixed @ 14.8 #/g & 1.34 yd. Circl 90 sks to pit. WOC 18 hrs. Test BOP to 500 psi. OK. Drill out w/ 17 1/2" bit.

10-04-02...TD'ed 17 1/2" hole @ 1300'. Ran 1300' 13 3/8" 48# J-55 ST&C casing. Cemented w/ 860 sks 65/35 C/Poz w/ 6% gel & additives. Mixed @ 12.5 #/g & 1.98 yd. Tailed w/ 200 sks C w/ 2% CaCl2. Mixed @ 14.8 #/g & 1.34 yd. Circl 150 sks to pit. WOC 18 hrs. Test BOP to 1000 psi. OK. Drill out w/ 12 1/4" bit.

10-11-02...TD'ed 12 1/4" hole @ 3010'. Ran 3010' 8 5/8" 32# J-55 ST&C casing. Cemented w/ 300 sks Thic-Set H & additives. Mixed @ 14.6 #/g & 1.52 yd. Followed w/ 900 sks 65/35 C/Poz w/ 6% gel & additives. Mixed @ 12.5 #/g & 1.96 yd. Tailed w/ 200 sks C w/ 2% CaCl2. Mixed @ 14.8 #/g & 1.34 yd. Did not Circl. WOC 6 hrs. Ran Temperature survey. TOC @ 2010'. Ran 1" & set 15 plugs using a total of 1200 sks Class C w/ CaCl2. Mixed @ 14.8 #/g & 1.34 yd. Circl 10 sks to pit on 15th plug. WOC 18 hrs. Test BOP to 2000 psi. OK. Drill out w/ 7 7/8" bit.

ACCEPTED FOR RECORD

NOV - 4 2002

ALEXIS C. SWOBODA  
PETROLEUM ENGINEER

14. I hereby certify that the foregoing is true and correct

Signed [Signature] Title N.M. Young District Manager Date 10/22/03

(This space for Federal or State office use)

Approved by \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_  
Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side

