

## MULTI-POINT SURFACE USE AND OPERATION PLAN

#1, Indian "A", 9201 JV-P

Page 2

### 4. Location of Existing and/ or Proposed Facilities if Well is Productive.

- A. If well is productive, we will use the existing well pad for the tank battery and all necessary production facilities.
- B. New facilities will be applied for via Sundry notice with a schematic diagram prior to installation.
- C. Should the well be successfully completed for production, the BLM will be notified within five days when the well is placed in producing status.
- D. All facilities will be painted a flat, nonreflective, earthtone color to match the standard environmental colors within six months of installation.

### 5. Location and Type of Water Supply

- A. Water for drilling and completion operations will either be purchased and trucked to the well site, or transported by plastic temporary "fas-line" laid on the surface alongside existing roads.

### 6. Source of Construction Materials

- A. Caliche used for construction of the drilling pad and access road will be obtained from closest existing caliche pit as designated by the BLM.
- B. If there is not sufficient material available, it will be purchased from the area designated by the BLM.

### 7. Methods of Handling Waste Disposal

- A. Drill cuttings will be disposed of in the reserve pits located on the east side of the rig.
- B. Drilling fluids will be allowed to evaporate in the reserve pits until the pits are dry enough for backfilling.
- C. Water produced during operations will be collected in tanks until hauled to an approved disposal system or a separate disposal application will be submitted to the BLM for appropriate approval.