

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NMOCL

FORM APPROVED

OMB No. 1004-0135

Expires: November 30, 2000

CISK

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Yates Petroleum Corporation

3a. Address

105 South Fourth Street, Artesia, NM 88210

3b. Phone No. (include area code)

(505) 748-1471

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980'FSL and 1250'FWL of Section 12-T22S-R23E

5. Lease Serial No.

NM-0251099-A

6. If Indian, Allottee, or Tribe Name

7. If Unit or CA. Agreement Designation

8. Well Name and No.

Smith Federal Gas Com #4

9. API Well No.

30-015-32470

10. Field and Pool, or Exploratory Area

Indian Basin Upper Penn

11. County or Parish, State

Eddy County, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/ Resume)	<input type="checkbox"/> Water Shut-off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other <u>Continuation of</u>
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and abandon	<input type="checkbox"/> Temporarily Abandon	<u>cementing surface casing</u>
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths or pertinent markers and sands. Attach the Bond under which the work will be performed or provide the Bond No. on file with the BLM/ BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notice shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

10/15/02 Ran 1". Tagged cement at 512'. Spotted 50 sx Class "C" + 2% CaCl2. Stopped pumping at 7:00 AM. WOC 1 hr. Ran 1" to 467'. Tagged cement at 476'. Spotted 50 sx Class "C" + 2% CaCl2. Stopped pumping at 8:00 AM. WOC 1 hr. Ran 1" to 414'. Tagged cement at 445'. Spotted 50 sx Class "C" + 2% CaCl2. Stopped pumping at 9:00 AM. WOC 1 hr. Ran 1" to 373'. Tagged cement at 396'. Spotted 50 sx Class "C" + 2% CaCl2. Stopped pumping at 10:00 AM. WOC 1 hr. Ran 1" to 310'. Tagged cement at 334'. Spotted 50 sx Class "C" + 2% CaCl2. Stopped pumping at 12:15 PM. WOC 2-1/4 hrs. Ran 1" to 310'. Tagged cement at 334'. Spotted 25 sx Class "C" + 2% CaCl2. Stopped pumping at 1:15 PM. WOC 1 hr. Ran 1" to 310'. Tagged cement at 332'. Spotted 25 sx Class "C" + 2% CaCl2. Stopped pumping at 2:15 PM. WOC 1 hr. Ran 1" to 310'. Tagged cement at 326'. Spotted 25 sx Class "C" + 2% CaCl2. Stopped pumping at 3:00 PM. WOC 1 hr. Ran 1" to 248'. Tagged cement at 276'. Spotted 25 sx Class "C" + 2% CaCl2. Stopped pumping at 4:00 PM. WOC 1 hr. Ran 1" to 279'. Tagged cement at 294'. Spotted 25 sx Class "C" + 2% CaCl2. Stopped pumping at 5:00 PM. WOC 1 hr. Ran 1" to 279'. Tagged cement at 289'. Spotted 25 sx Class "C" + 2% CaCl2. Stopped pumping at 6:00 PM. WOC 1 hr. Ran 1" to 279'. Tagged cement at 286'.

CONTINUED ON NEXT PAGE:

14. I hereby certify that the foregoing is true and correct.

Name (Printed/ Typed)

Tina L. Huerta

Signature

Title

Regulatory Compliance Supervisor

Date

October 30, 2002

ACCEPTED FOR RECORD

NOV 4 2002

Approved by

Title

Date

Conditions of approval, if any are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

LES BABYAK
PETROLEUM ENGINEER


Title 18 U.S.C. Section 1001 AND Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on reverse)

YATES PETROLEUM CORPORATION
Smith Federal Gas Com #4
Section 12-T22S-R23E
Eddy County, New Mexico

SUNDRY NOTICE CONTINUED:

Spotted 25 sx Class "C" + 2% CaCl₂. Stopped pumping at 7:00 PM. WOC 1 hr. Ran 1" to 279'. Tagged cement at 282'. Spotted 25 sx Class "C" + 2% CaCl₂. Stopped pumping at 7:45 PM. WOC 3/4 hrs. Ran 1" to 248'. Tagged cement at 279'. Spotted 25 sx Class "C" + 2% CaCl₂. Stopped pumping at 7:45 PM. WOC 3/4 hrs. Ran 1". Tagged cement at 270'. Spotted 25 sx Class "C" + 2% CaCl₂. Stopped pumping at 9:00 PM. WOC 1-1/4 hrs. Ran 1" to 217'. Tagged cement at 243'. Spotted 25 sx Class "C" + 2% CaCl₂. Stopped pumping at 10:00 PM. WOC 1 hr. Ran 1" to 125'. Tagged cement at 140'. Spotted 150 sx Class "C" Neat. Stopped pumping at 2:30 AM 10/16/02. WOC 4-1/2 hrs. Circulated 25 sx to pit. NOTE: 1" cement job witnessed by Don Early with BLM in Carlsbad. WOC 51 hours and 30 mins. Reduced hole to 7-7/8" and resumed drilling.


Tina Huerta
Regulatory Compliance Supervisor
October 30, 2002