

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Martin Yates III</u>		Lease <u>Belle Macord</u>		Well # <u>2-A</u>	
Location of Well	Unit <u>F</u>	Section <u>22</u>	Township <u>23S</u>	Range <u>26E</u>	County <u>EDDY</u>
Drilling Contractor	<u>Harvey E. Yates</u>		Type of Equipment		
<u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>4</u>	<u>8 5/8</u>		<u>new</u>	<u>525</u>	<u>100</u>
	<u>5 1/2</u>		<u>new</u>	<u>1900</u>	<u>50</u>
Casing Data:					
Surface _____ joints of _____ inch _____ # Grade _____					
(Approved) (Rejected) _____					
Inspected by _____ date _____					
Cementing Program					
Size of hole _____ Size of Casing _____ Sacks cement required _____					
Type of Shoe used <u>float</u> Float collar used <u>NO</u> Btm 3 jts welded _____					
TD of hole <u>1432</u> Set <u>9.1</u> Feet of <u>7</u> Inch <u>20</u> # Grade <u>25-4PI</u>					
New-used csg. @ _____ with <u>50</u> sacks neat cement around shoe					
+ _____ sax _____ additives <u>2% Calcium Chloride</u>					
Plug down @ <u>2:45</u> (AM) (PM) Date <u>12-29-61</u>					
Cement circulated <u>no</u> No. of Sacks _____					
Cemented by <u>Denton</u> Witnessed by <u>L O B L F V</u>					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ <u>*</u> (AM) (PM) Date <u>not required on this string</u>					
Method used _____ Witnessed by _____					
Remarks: <u>* This well is in the shallow water area.</u>					
<u>1. 1910' cut + pulled 7" at 1400'</u>					
<u>1. 25 sk. plug from 1910' to 1965'</u>					
<u>15 sk. plug 1400' to 1355'</u>					
<u>15 sk. plug. 480' to 435'</u>					

Hole loaded
with mud.

8' hole
8' south of this
well was plugged

plugged by Denton 1-8-62

Witnessed by H.L.

This well to be retained for water well