

FT. per sk. Fill up

8" Hole = 3.1516

7" Casing 10" = 4.837

NEW MEXICO OIL CONSERVATION COMMISSION

DRAWER DD

ARTESIA, NEW MEXICO

2073
125
1948

PLUGGING
FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Martin Yates III</u>		Lease <u>Belle McCord</u>		Well # <u>I</u>	
Location of Well	Unit <u>SWNW</u>	Section <u>22</u>	Township <u>235</u>	Range <u>26E</u>	County <u>EDDY</u>
PLUGGING Drilling Contractor	<u>CO. TOOLS + Denton</u>		Type of Equipment <u>PULLING UNIT</u>		

APPROVED CASING in Hole WHEN PLUGGED

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
	7"	20#	NEW	1993	300
Temp. survey shows top cement at				255'	
					T.D. 2073'

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole _____ Size of Casing _____ Sacks cement required _____

Type of Shoe used _____ Float collar used _____ Btm 3 jts welded _____

TD of hole 1993 Set _____ Feet of _____ Inch _____ # Grade _____

New-used csg. @ _____ with _____ sacks neat cement around shoe

+ _____ sax _____ additives _____

Plug down @ _____ (AM) (PM) Date _____

Cement circulated _____ No. of Sacks _____

Cemented by _____ Witnessed by _____

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

plugged as follows.

1. 25 sks. 2073' to 1943'

2. 15 sks. 1400' to 1355'

3. 15 sks. 480' to 435'

plugged by Denton + witnessed

by Moore Jan. 14, 1962

Gravel at 185', and coarse sand & gravel at 180'.

2. 1420 to 1490 15 ft. at base of reef.

3. 725-2797 15 ft. 7 ft. of reef.