


N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico



WELL RECORD

HOBBS OFFICE

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

AREA 640 ACRES
LOCATE WELL CORRECTLY

D. C. De Vito

P.O. Box 645, Midland, Texas

State 1 Company or Operator NEARBY Address 19 T. 23
Well No. 1 in NEARBY of Sec. 19
Lease 26a. N. M. P. M. Wildcat Field, Eddy County.
Well is 660 feet south of the North line and 660 feet west of the East line of section 19
If State land the oil and gas lease is No. B-9546 Assignment No. Original
If patented land the owner is _____ Address _____
If Government land the permittee is _____ Address _____
The Lessee is D. C. De Vito Address Midland, Texas.
Drilling commenced March 7 19 46 Drilling was completed June 15 19 46
Name of drilling contractor Harvey Yates Address Artesia, New Mexico
Elevation above sea level at top of casing 3408 feet.
The information given is to be kept confidential until X 19 _____

OIL SANDS OR ZONES

No. 1, from NONE to _____ No. 4, from _____ to _____
No. 2, from _____ to _____ No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 1760 to 1780 feet. Salt Water
No. 2, from 1820 to 1870 feet. Salt Water
No. 3, from _____ to _____ feet. _____
No. 4, from _____ to _____ feet. _____

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
<u>12 1/2</u>	<u>50</u>	<u>8</u>	<u>14</u>	<u>21</u>					
<u>8 1/2</u>	<u>28</u>	<u>8</u>	<u>"</u>	<u>21 1/2</u>	<u>Texas</u>				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED

PLUGS AND ADAPTERS

Heaving plug—Material Cement Length 2-30 foot plugs. Depth Set 1650' and 300'
Adapters—Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment: _____

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet
Cable tools were used from 0 feet to 2753 feet, and from _____ feet to _____ feet

PRODUCTION

Put to producing _____, 19 _____

The production of the first 24 hours was _____ barrels of fluid of which _____ % was oil; _____ % emulsion; _____ % water; and _____ % sediment. Gravity, Be. _____
If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____
Rock pressure, lbs. per sq. in. _____

EMPLOYEES

I. H. Hancock, Driller S. E. Sims, Driller
Harold Hancock, Driller _____, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 15th.day of June, 19 46R. H. Hammer
Notary PublicMy Commission expires January 2, 1950Carlsbad, New Mexico, June 15 1946.

Place Date

Name R. E. Sims

Position _____

Representing _____

Company or Operator

Address P.O. Box 645, Midland, Texas.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	210	210	Sand, Gravel and Lime Boulders.
210	230	20	Anhydrite and Red Beds.
230	1160	930	Anhydrite
1160	1260	100	Anhydrite and Lime
1260	1280	20	Anhydrite
1280	1397	117	Anhydrite and Lime.
1397	1420	23	Black Lime Top of Delaware Line 1397
1420	1460	40	Lime, Sand and trace of Shale
1460	1600	220	Black and Grey Lime
1600	1790	190	Sand, anhydrite and water
1790	1820	30	Water
1820	1870	50	Shale and Lime
1870	1930	70	Sand.
1930	1995	45	White and Buff Lime
1995	2197	202	Sand, Shale and Lime
2197	2367	170	Lime
2367	2380	13	Sand, Shale and Lime
2380	2425	45	Brown and Buff Lime with trace of sand and shale
2425	2445	20	Grey Shale and Sand
2445	2490	45	Buff to light Lime
2490	2570	80	Grey Shale and loose Sand.
2570	2625	55	Black to dark grey Lime
2625	2635	10	Grey Shale and sand.
2635	2660	25	Black to dark Grey Lime.
2660	2670	10	Grey Shale and Sand.
2670	2704	34	Black and Grey Lime, Shale and Sand.
2704	2716	12	Black Cal. Shale and Sand with trace of Lime.
2716	2753	37	