

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Grid for locating well correctly. AREA 640 ACRES. LOCATE WELL CORRECTLY.

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

Martin & Lycette, Carlsbad, New Mexico
Pardue, Well No. 1 in SE SW NW of Sec. 29, T. 24
R. 26, N. M. P. M., wildcat Field, Addy County.
Well is 2310 feet south of the North line and 990 feet west of the East line of sec 29
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is Pardue & Guitar, Address Loving, N M
If Government land the permittee is, Address
The Lessee is Yates & Dooley, Address Artesia, N M
Drilling commenced Oct. 1 19 38 Drilling was completed Nov 5 19 38
Name of drilling contractor Martin & Lycette, Address Carlsbad, N M
Elevation above sea level at top of casing 3442 feet.
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 1671 to 1875 No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.
No. 1, from none to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

Table with 9 columns: SIZE, WEIGHT PER FOOT, THREADS PER INCH, MAKE, AMOUNT, KIND OF SHOE, CUT & FILLED FROM, PERFORATED FROM TO, PURPOSE. Includes 'none' in THREADS PER INCH.

MUDDING AND CEMENTING RECORD

Table with 7 columns: SIZE OF HOLE, SIZE OF CASING, WHERE SET, NO. SACKS OF CEMENT, METHOD USED, MUD GRAVITY, AMOUNT OF MUD USED.

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

Table with 7 columns: SIZE, SHELL USED, EXPLOSIVE OR CHEMICAL USED, QUANTITY, DATE, DEPTH SHOT OR TREATED, DEPTH CLEANED OUT.

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet
Cable tools were used from 0 feet to 1875 feet, and from feet to feet

PRODUCTION

Put to producing, 19
The production of the first 24 hours was barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

E. P. Moran, Driller A. E. Lycette, Driller
Coleman Kerr, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Mentone Texas 11-14-38
Subscribed and sworn to before me this 14th day of November, 19 38
Name A. E. Lycette Position Driller

## FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	5	5	Surface soil
5	30	25	Caliche
30	107	77	Clay
107	126	19	Soft Lime
126	138	12	Gray shale
138	1010	872	Anhy & gyp
1010	1140	130	Salt
1140	1150	10	Gray lime
1150	1552	402	Anhy
1552	1671	119	Lime
1671	1746	75	Sand
1746	1833	87	Lime
1833	1875	42	Sand
			Hole full of salt water Abandoned.