NEW MEXICO STATE LAND C-FICE

Dufli cali

Santa Fe, New Mexico

DEPARTMENT OF THE STATE GEOLOGIST NOTICE OF INTENTION TO DRILL NEW WELL

Notice must be given to the State Geologist or to the proper Oil and Gas Inspector and approval obtained before drilling begins. If changes in the proposed plan are considered advisable a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval

such changes will be ret				•
following approval. Mr. E. H. Wells		Carls'	bad N. Mex	, <u>Jan. 20</u> 19 33
Mr. E. H. Wells	, State	Geologist.	to commence the dr	illing of a well to be
Dear Sir: You are known as The Pool	e hereby notified th	at it is our intention	in SE	illing of a well to be
known as The Pool T. 22 S , R. 2	OII & Gas OU.	D. M.		Oil Field
T. 22 S , R. 2	7 E , N. M.	Country		
h		County	(N.) couth	the and sht 300t
N.	The we	ell is abt 300 fe	et (S.) of South	line and abt 300t
	(K)			
	(W.)	st line of Sec	. 16. T. 22 S.	R 27 E N.M.P.M
	ot	Give location from se	ection or other legal	subdivision lines. Cross
	Out W	ong directions.)		
16	I dat wa	state land the oil and	1 gas lease is No	B-345
	Assign	ment No.		
	Assign	inicit ino.	wner is	
AREA 640 ACRES	A	ddress		1
The lesses is The I	Pool Oil & Ga	s Co Addres	s Carlsbad, N	ew Mexico
The elevation of t	he derrick floor abo	ove sea level is 3,11	.0 feet. We pr	ropose to drill well with
No. H Ft Worth	Bpudder			
	Make of Drill			• 1• 1-1
We propose to use	the following strin	gs of casing and to la	and or cement them as	s indicated.
Size of Casing	Weight Per Foot	New or Second Hand		Landed or Cemented
	Weight Per Foot			
8 1 in.		New or Second Hand	Depth	Landed or Cemented
8 1 in.		New or Second Hand	Depth	Landed or Cemented
8 ¹ in.	ICATE	New or Second Hand once run	Depth 219 feet	Landed or Cemented Landed or landing casing. We
8¼ in. If changes in the above	re plan become advi	once run	Depth 219 feet you before cementing	Landed or Cemented Landed or landing casing. We 2150 feet.
84 in. If changes in the abovestimate that the first	re plan become advi	once run sable we will notify y as sand should occur	Depth 219 feet you before cementing at a depth of about	Landed or Cemented Landed or landing casing. We 2150 feet. 10" tools to 219; 5
84 in. If changes in the above estimate that the first Additional information	re plan become advi productive oil or ga an: This well	once run sable we will notify y as sand should occur was drilled fo	Depth 219 feet you before cementing at a depth of about r potash with	Landed or Cemented Landed or landing casing. We 2150 feet. 10" tools to 219' 5 for a complete
84 in. If changes in the above estimate that the first Additional information where 84 pipe h	re plan become advi productive oil or ga n: This well was been land	once run sable we will notify y as sand should occur was drilled fo ed by the Pool	Depth 219 feet you before cementing at a depth of about r potash with Oil & Gas Co.	Landed or Cemented Landed or landing casing. We 2150 feet. 10" tools to 219' 5 for a complete feet. This hole
8 in. If changes in the above estimate that the first Additional information where 8 in pipe howater shut off.	re plan become advi productive oil or ga n: This well was been land A potash co	once run sable we will notify y as sand should occur was drilled fo ed by the Pool re hole was dr	Depth 219 feet you before cementing at a depth of about r potash with Oil & Gas Co. illed to 696 i	Landed or Cemented Landed or landing casing. We 2150 feet. 10" tools to 219' 5 for a complete feet. This hole tools and is now
If changes in the above estimate that the first Additional information where 84 pipe howater shut off. has been rimmed	re plan become advi productive oil or ga an: This well was been land A potash con down by the	once run sable we will notify y as sand should occur was drilled fo ed by the Pool re hole was dr Pool Oil & Gas	Depth 219 feet You before cementing at a depth of about r potash with Oil & Gas Co., illed to 696 if Co. with 81%	Landed or Cemented Landed or landing casing. We 2150 feet. 10" tools to 219! 3 for a complete feet. This hole tools and is now will be continued
If changes in the above estimate that the first Additional information where 84 pipe howater shut off. has been rimmed drilling below in the state of the state o	re plan become adviproductive oil or gan: This well was been landed A potash condown by the indry hole is after which	once run sable we will notify y as sand should occur was drilled fo ed by the Pool re hole was dr Pool Oil & Gas n salt at 1,11 seat will be m	Depth 219 feet You before cementing at a depth of about r potash with Oil & Gas Co. illed to 696 illed t	Landed or Cemented Landed or landing casing. We 2150 feet. 10" tools to 219' 5 for a complete feet. This hole tools and is now will be continued casing if needed.
If changes in the above estimate that the first Additional information where 84" pipe howater shut off. has been rimmed drilling below in thru salt beds, 84" pipe is ab	re plan become adviproductive oil or gan: This well was been landed A potash coldown by the indry hole is after which ove all salt	once run sable we will notify y as sand should occur was drilled fo ed by the Pool re hole was dr Pool Oil & Gas a salt at 1,11 seat will be SM beds.	Depth 219 feet You before cementing at a depth of about r potash with Oil & Gas Co. illed to 696 illed t	Landed or Cemented Landed or landing casing. We 2150 feet. 10" tools to 219' 5 for a complete feet. This hole tools and is now will be continued casing if needed. & GAS COMPANY
If changes in the above estimate that the first Additional information where 84" pipe howater shut off. has been rimmed drilling below in thru salt beds, 84" pipe is ab	re plan become adviproductive oil or gan: This well was been landed A potash coldown by the indry hole is after which ove all salt	once run sable we will notify y as sand should occur was drilled fo ed by the Pool re hole was dr Pool Oil & Gas a salt at 1,11 seat will be SM beds.	Depth 219 feet You before cementing at a depth of about r potash with Oil & Gas Co. illed to 696 illed t	Landed or Cemented Landed or landing casing. We 2150 feet. 10" tools to 219! 3 for a complete feet. This hole tools and is now will be continued
If changes in the above estimate that the first Additional information where 84 pipe howater shut off. has been rimmed drilling below in the state of the state o	re plan become adviproductive oil or gan: This well was been landed A potash coldown by the indry hole is after which ove all salt	once run once run sable we will notify y as sand should occur was drilled fo ed by the Pool re hole was dr Pool Oil & Gas as salt at 1,11 seat will be sw beds. Ig. By	Depth 219 feet You before cementing at a depth of about r potash with Oil & Gas Co. illed to 696 if Co. with 81 of feet, which add for 5/8 of the pool OIL	Landed or Cemented Landed or landing casing. We 2150 feet. 10" tools to 219' 5 for a complete feet. This hole tools and is now will be continued casing if needed. & GAS COMPANY Company or Operator.
If changes in the above estimate that the first Additional information where 84" pipe howater shut off. has been rimmed drilling below in thru salt beds, 84" pipe is ab	re plan become adviproductive oil or gan: This well was been landed A potash coldown by the indry hole is after which ove all salt	once run once run sable we will notify y as sand should occur was drilled fo ed by the Pool re hole was dr Pool Oil & Gas n salt at 1,11 seat will be SW beds. 19	Depth 219 feet You before cementing at a depth of about r potash with Oil & Gas Co. illed to 696 if Co. with 84 if O feet, which add for for 6-5/8 if THE POOL OIL on Secty-Trea	Landed or Cemented Landed I Landed Or landing casing. We 2150 feet. 10" tools to 219' 5 for a complete feet. This hole tools and is now will be continued casing if needed. & GAS COMPANY Company or Operator. Scott Etter s.
If changes in the above estimate that the first Additional information where 8th pipe howater shut off. has been rimmed drilling below in thru salt beds, 8th pipe is ab Approved Except as follows:	re plan become adviproductive oil or gan: This well was been landed A potash condown by the indry hole in after which over all salt	once run once run sable we will notify y as sand should occur was drilled fo ed by the Pool re hole was dr Pool Oil & Gas n salt at 1,11 seat will be SM beds. 19	Depth 219 feet You before cementing at a depth of about r potash with Oil & Gas Co. illed to 696 if Co. with 8½* O feet, which lada for 5/8. THE POOL OIL on Sec y-Treaccommunication regard	Landed or Cemented Landed or landing casing. We 2150 feet. 10" tools to 219' 5 for a complete feet. This hole tools and is now will be continued casing if needed. & GAS COMPANY Company or Operator. Scott Etter ding well to
If changes in the above estimate that the first Additional information where 8th pipe howater shut off. has been rimmed drilling below in thru salt beds, 8th pipe is ab Approved Except as follows:	re plan become adviproductive oil or gan: This well was been landed A potash coldown by the indry hole is after which ove all salt	once run once run sable we will notify y as sand should occur was drilled fo ed by the Pool re hole was dr Pool Oil & Gas n salt at 1,11 seat will be simpleds. Inspector. By Positi	Depth 219 feet You before cementing at a depth of about r potash with Oil & Gas Co. illed to 696 if Co. with 8½* O feet, which lade for 6-5/8 THE POOL OIL on Sec'y-Treacommunication regard	Landed or Cemented Landed or landing casing. We 2150 feet. 10" tools to 219' 5 for a complete feet. This hole tools and is now will be continued casing if needed. & GAS COMPANY Company or Operator. Scott Etter ding well to
If changes in the above estimate that the first Additional information where 8th pipe howater shut off. has been rimmed drilling below in thru salt beds, 8th pipe is ab Approved Except as follows:	re plan become adviproductive oil or gan: This well was been landed A potash condown by the indry hole in after which over all salt	once run once run sable we will notify y as sand should occur was drilled fo ed by the Pool re hole was dr Pool Oil & Gas n salt at 1,11 seat will be simpleds. Inspector. By Positi	Depth 219 feet you before cementing at a depth of about. r potash with Oil & Gas Co. illed to 696 i Co. with 81 of feet, which aday for \$6-5/8 of the POOL OIL on Sec!y-Treacommunication regard Scott Ette cos Carlsbad,	Landed or Cemented Landed or landing casing. We 2150 feet. 10" tools to 219' 5 for a complete feet. This hole tools and is now will be continued casing if needed. & GAS COMPANY Company or Operator. Scott Etter ding well to