Borted 7/1/88)

	╾┼╼╌┠╌		NEW MEXICO OIL CONSERVATION COMMISSION
<b> ∤∤</b> -	╶┼╾╂╸	┼╌┾╌╉━╸	NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico
		<del></del>	- ECE
			WELL RECORD JUL 28 1961
			WELL RECORD JUL
-+-+-	0		Mail to District Office, Oil Conservation Commission, to which Forms E-foil was sent not
		┼╾┼╌┽	- Station Division Office Oil Commission on which Form to 101 was sent not
<del> </del> <b> </b>	╶┼╌╬╌	┼╌┼─┼─	later than twenty days after completion of well. Follow instructions in Rules and Regulations
			of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies
LOCA	AREA 640 A TE WELL C	CRES CORRECTLY	
•			crocration Crawford
	ш <b>е</b> лр.та	(Company or O	rporation Crawford (Lease)
Well No	1	in ME	
			Pool, Eddy. County.
		(	
Well isl.,	780	feet from	n South line and 1,980 feet from West
of Section	9	I	f State Land the Oil and Gas Lesse No. is
			21
			Brown Drilling Company
			131, Midland, Texas
			bing Head
Jani	ary10	<b>.</b>	
			OIL SANDS OR ZONES
			tototo
No. 2. from			totototo

	,	
No. 3	, from <b>to</b>	No. 6, fromto

### IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from		feet.	F.L.500 feet from surface
No. 2, from			
No. 3, from	to	feet.	
No. 4, from	to	feet.	

## CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOL	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
7 inch	17	New	343 feet				Surface casing
41 inch	9.5	New	2196 feat	Baker		2169-74 feet	Production
						21 feet	

#### MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CABING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD Gravity	AMOUNT OF MUD USED
8 3/4"	761	343 feat	75	Circ. to surf.		
-6 1/4"	411	2196 Feet	35	Spotted on bott	om	

# **BECORD OF PRODUCTION AND STIMULATION**

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

2174!, w/1000.gals. 440 Lesse Crude and 1000# sand Fraced Perfs w/5000 gals. 240 ref

011 and 5000# 10-40 sand. Parf. 2169-74' w/2 jets per ft. (Flash Perf.) Recovered all

----LQ.

# REALAD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

	TOOLS	USED		
Rotary tools w	ere used from	feet, and from	feet to	fcet.
Cable tools we	re used fromfeet to	feet, and from	feet to	feet.
	PBODUC	TION		
Put to Produci	ng, 19			
OIL WELL:	The production during the first 24 hours was	barrels of li	iquid of which	
	was oil;% was emulsior;	% water; and	% was sed	iment. A.P.I.
	Gravity			
GAS WELL:	The production during the first 24 hours was	M.C.F. plus		barrels of
	liquid Hydrocarbon. Shut in Pressurelbs.			
Length of Tim	e Shut in			

#### PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE): Southeastern New Mexico Northwestern New Marian

					Northwestern New Mexico
Т.	Anhy	Т.	Devonian	Т.	Ojo Alamo
Τ.	Salt	Т.	Silurian		Kirtland-Fruitland
B.	Salt	Т.	Montoya		Farmington
Т.	Yates	Т.	Simpson		Pictured Cliffs
Т.	7 Rivers	Т.	McKee		Menefee
Т.	Queen	Т.	Ellenburger		
Т.	Grayburg	Т.	Gr. Wash		Mancos
	San Andres		<b>.</b> .		Dakota
Т.	Glorieta				Morrison
Т.	Drinkard	Т.	Castile 1558	Т.	Penn
Т.	Tubbs	Т.	Lamar Shale 2073	T.	
Т.	Abo	Т.	Lamar ls 2102	T	
Т.	Penn	Т.	Ramsay ss 2151	T	
	Miss	T.		т.	

## FORMATION RECORD

From	То	Thickness in Feet	Formation	From	То	Thickness in Feet	Formation
0 1277 1558 1645 1850 2073 2102 2151	1277 1558 1645 1850 2073 2102 2151 2198	1277 281 87	Anhydrite Salt Anhydrite Salt Anhydrite Shale and limestone Is and shly ss ss			5 A	CE FICE
					N		particular and a second se

# ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

July 17, 1961 (Date)

Company or Operator. Cabeen Exploration Corporation Address....747. Petroleum Bldg, Roswell, New Mexico Name Manuel Position Division Manager