

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICOMidland, Texas  
(Place)November 7, 1952  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

C. D. Donaho  
(Company or Operator)

Well No. 1

in

M  
(Unit)

SW

1/4

SW

1/4

of Sec. 8

T. 24-S

R. 28-E

NMPM,

Wildcat

Pool

(40-acre Subdivision)

Eddy

County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

It is our intention, as soon as approval is granted to recover as much casing as possible (Approximately 120' of 10 3/4" and (2100' of 7") and then commence plugging operations using the pump and tubing method. The Hobbs Pipe and Supply Co. should have a machine available to do this work sometime within the next 10 days.

Tentative Plugging Program: Set cement plug at 2450' to 2500'. Cut and pull 7" casing from approximately 2100'; run tubing and load hole with mud laden fluid. Spot a 20' cement plug at top of 7" casing; 20' cement plug at 1150'; cement plug at 280' to 330'. Cut and pull 120' of 10-3/4" casing, fill with mud to surface. Clean up location and fill pits and set 4" x 5' pipe marker in cement in top of hole.

NOV 14 1952

Approved....., 19.....  
Except as follows:

C. D. Donaho

Company or Operator

By..... G. W. Green

Position..... Division Landman

Send Communications regarding well to:

Approved  
OIL CONSERVATION COMMISSION

By.....

Name.....

G. W. Green

Title.....

Address.....

313 N. Colorado St.  
Midland, Texas

7

© 2000 Blackwell Science Ltd *Journal of Internal Medicine* 247: 105–112