

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Albert F. Schnabel
Company or Operator
Well No. 1 in NE 1/4 of Sec. 11, T. 24 S. R. 28 E., N. M. P. M., Wilcox Field, Ledy County.
Well is 355 feet south of the North line and 645 feet west of the East line of Section 11
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is C. F. Beeman, Address Malaga, N. Mex.
If Government land the permittee is, Address
The Lessee is Albert F. Schnabel, Address Bethany, Oklahoma
Drilling commenced 12 March 19 52 Drilling was completed 17 April 19 52
Name of drilling contractor G. A. Martin, Address Midland, Texas
Elevation above sea level at top of casing 2967.8 feet.
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from to No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.
No. 1, from 60 to 68 feet.
No. 2, from 1290 to 1295 feet.
No. 3, from 2730 to 2749 feet.
No. 4, from 2825 to 2844 feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED TO	PURPOSE
13-3/8	54 1/2			262	Texas			Surface
7"	26 1/2			2619	"			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet.
Cable tools were used from 0 feet to 3016 feet, and from feet to feet.

PRODUCTION

Put to producing 19
The production of the first 24 hours was barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

I. G. Warren Driller Roy Blackstock Driller
E. W. Sutton Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Carlsbad, N. M. 4-24-52
Name Albert F. Schnabel
Position Owner
Representing Albert F. Schnabel
Company or Operator.
Address Box 91, Bethany, Oklahoma

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	6	6	Caliche
6	60	54	Soil
60	120	60	Gravel & Shale
120	135	15	Lime
135	150	15	Shale
150	290	140	Lime
290	300	10	Shale
300	325	25	Lime
325	330	5	Shale
330	345	15	Lime
345	370	35	Anhydrite
370	385	15	Salt
385	395	10	Anhydrite
395	460	65	Salt
460	470	10	Anhydrite
470	490	20	Salt
490	500	10	Anhydrite
500	595	95	Salt
595	625	30	Anhydrite
625	755	130	Salt
755	765	10	Shale
765	790	25	Lime & Salt
790	835	20	Anhydrite
835	865	30	Salt
865	960	95	Anhydrite & Salt
960	965	5	Salt
965	1290	325	Anhydrite
1290	1295	5	Lime
1295	1345	50	Sand
1345	1355	10	Anhydrite
1355	1372	17	Salt
1372	1385	13	Anhydrite
1385	1435	50	Salt
1435	1575	140	Lime
1575	1720	145	Anhydrite
1720	1765	45	Lime
1765	1733	23	Anhydrite
1788	1970	182	Salt
1970	2057	87	Lime
2057	2370	313	Salt
2370	2395	25	Anhydrite
2395	2599	204	Lime
2599	2630	31	Black Lime
2630	2885	255	Del. Sand
2885	2914	29	Black Lime
2914	2953	39	Del. Sand
2953	3016	63	Del. Sand