NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

	Indicate Nature of Report by Checking Bo	elow.
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON REPAIRING WELL
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLETION OPERATION	REPORT ON (Other)
	February 7, 1	953 Lubbock, Texas
	(Date)	(Place)
Following is a report on the work of	done and the results obtained under the heading	noted above at the
DeKalb Agricultural Assn.	Inc. C.	P. Pardue "Z"
(Company or Oper	, Well No l-21	in the SE 1/4 NE 1/4 of Sec. 21
T 24 S , R 28 E , NMPM.,	Wildcat Pool,	Ecidy County
The Dates of this work were as follows:	Pebruary 7, 1953	
Notice of intention to do the work (was)	not) submitted on Form C-102 on	chruary 6 , 19.53
and approval of the proposed plan (was)	(was not) obtained.	
DETAIL	ED ACCOUNT OF WORK DONE AND RES	ULTS OBTAINED
	ED ACCOUNT OF WORK DONE AND RES	ULTS OBTAINED
February 7, 1953:		
February 7, 1953:	ED ACCOUNT OF WORK DONE AND RES	
February 7, 1953: Total depth 3151. Set	304 of 8-5/8" casing and cemen	ted with 125 sacks of
February 7, 1953: Total depth 315. Set 6% Gel. Tested casing	304° of 8-5/8" casing and cemen at 8:00 A. M. 2-7-53. Applied	ted with 125 sacks of
February 7, 1953: Total depth 3151. Set 6% Gel. Tested casing	304 of 8-5/8" casing and cemen	ted with 125 sacks of
February 7, 1953: Total depth 3151. Set 6% Gel. Tested casing	304° of 8-5/8" casing and cemen at 8:00 A. M. 2-7-53. Applied	ted with 125 sacks of
February 7, 1953: Total depth 3151. Set 6% Gel. Tested casing	304° of 8-5/8" casing and cemen at 8:00 A. M. 2-7-53. Applied	ted with 125 sacks of
February 7, 1953: Total depth 3151. Set 6% Gel. Tested casing	304° of 8-5/8" casing and cemen at 8:00 A. M. 2-7-53. Applied	ted with 125 sacks of
February 7, 1953: Total depth 3151. Set 6% Gel. Tested casing	304° of 8-5/8" casing and cemen at 8:00 A. M. 2-7-53. Applied	ted with 125 sacks of
February 7, 1953: Total depth 315'. Set 6% Gel. Tested casing and there was no drop i	304° of 8-5/8" casing and cemen at 8:00 A. M. 2-7-53. Applied	ted with 125 sacks of 500# pressure for one hour rill ahead.
February 7, 1953: Total depth 3151. Set 6% Gel. Tested casing	304 of 8-5/8" casing and cemen at 8:00 A. M. 2-7-53. Applied in pressure. Now preparing to d	ted with 125 sacks of 500# pressure for one hour rill ahead.
February 7, 1953: Total depth 315'. Set 6% Gel. Tested casing and there was no drop i	304 of 8-5/8" casing and cemen at 8:00 A. M. 2-7-53. Applied in pressure. Now preparing to d	ted with 125 sacks of 500# pressure for one hour rill ahead. Driller (Title) that the information given above is true and comple
February 7, 1953: Total depth 315'. Set 6% Gel. Tested casing and there was no drop i	304 of 8-5/8" casing and cemen at 8:00 A. M. 2-7-53. Applied in pressure. Now preparing to decompany) S. & W. Drilling Continuous C	ted with 125 sacks of 500# pressure for one hour rill ahead. Driller (Title) that the information given above is true and complete whowledge.
February 7, 1953: Total depth 315'. Set 6% Gel. Tested casing and there was no drop i	304 of 8-5/8" casing and cemen at 8:00 A. M. 2-7-53. Applied in pressure. Now preparing to decompany. S. & W. Drilling Conception of the best of my commission.	ted with 125 sacks of 500# pressure for one hour rill ahead. Driller (Title) that the information given above is true and complete knowledge.
February 7, 1953: Total depth 315'. Set 6% Gel. Tested casing and there was no drop i	304 of 8-5/8" casing and cemen at 8:00 A. M. 2-7-53. Applied in pressure. Now preparing to decompany. S. & W. Drilling Co. (Company) I hereby certify to the best of my Name. DEKALE Position	ted with 125 sacks of 500# pressure for one hour rill ahead. Driller (Title) that the information given above is true and completely knowledge.

COLUMN FRANCISCO DEFINITION OF THE CONTROL OF THE C