NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

Notice of Intention to Change Plans		Notice of Intention to Temporarily Abandon W	/ELL	Notice of To Drill D			
NOTICE OF INTENTION TO PLUG WELL	x	Notice of Intention to Plug Back		Notice of to Set Lini			
Notice of Intention to Squeeze		Notice of Intention to Acidize		NOTICE OF			
Notice of Intention to Gun Perforate		Notice of Intention (Other)		Notice of I (Other)	INTENTION		
OIL CONSERVATION COM SANTA FE, NEW MEXICO Gentlemen:	IMISSION	Hobba (Place	BevMexic	2 0	Jul (Date	y 24.	1 963
		certain work as described b					
(Comp	any or Operator	NY Va	Leese	Well No		in	(Unit)
4	Sec7	, T 24-5 , R	29-1 ,NMPM	r., Ma .]	8 58	••••••	Pool
	Coı	inty.					
See attached pro	(FOLLOW	L DETAILS OF PROP INSTRUCTIONS IN TH plug and abandon.	E RULES AND		1 5)		
					RE	CEI	VED.
					JL	JL 2 5	1963
						0. C.	
JUL 2.5			TENNECO CO TENNECO OI		ey its ma	RACING	AGENT
Except as follows:		By	, au	Lang	-	A. W. I	ang

Approved

Title.....

By

OIL CONSERVATION COMMISSION

1211

WIL ARD GAS INSPECTOR

11

21119

Address. P. O. Box 279, Hobbs, New Maxico, 88240

ARTESI	A DISTRICT OFFI			
No. Copies Resolved				
D133418U-3331				
	тіс. 1 с			
GRA OR				
an di k Fe				
ACCOMPCIAL STREET	· · - · ·			
STATE CAME O HO	4. 4.			
J 3 6.3.				
FLAR OF DECES				
	1			
BURGER OF ATNES				

TENNECO OIL COMPANY PROGNOSIS TO PLUG AND ABANDON July 24, 1963

Lease: : Valley Land

Well No.: 3

Location: 1650' NSL and 1650' EWL, Sec. 7, T-24-S, R-29-E, Eddy County, New Mexico

Well Data:

- 1. Elevation: 2949' KB, 2943' GL
- 2. Zero Datum: 6' above GL-
- 3. TD: 2797' PBTD: 2774'
- 4. Perforations: 2755' 2766' w/6 shots/ft
- 5. Stimulation: Fraced 1500 gals crude oil w/1500# Ottawa sd
- 6. Casing: 8 5/8", 38#, H-40 set @ 313' w/200 sx. Cmt circulated. 5 1/2", 14#, J-55, set @ 2796' w/100 sx cmt. Top of cmt 1950'.
- 7. Previous Workover: None

Procedure:

- 1. Pull rods and tbg.
- 2. Spot 25 sk plug @ PBED 2774'.
- 3. Cut 5 1/2" csg @ approx 1950'.
- 4. Spot 20 sk plug from 2400' to 2500'. Bottom of salt @ 2466'.
- 5. Spot 20 sk plug from 1900' to 2000' or 50' on either side of csg stub.
- 6. Spot 20 sk plug from 450' to 550'. Top of salt @ 500'.
- 7. Spot 10 sk plug in top of surface w/dry hole marker.
- 8. Clean and level location for state inspection. RECEIVED

JUL 2 5 1963

NOTE: The hole must be filled w/mud between all plugs.

CFT/1b