| L | Form 9-881 a. (Feb. 1951) | | DEPART | INHORCE (SUBMIT IN TRIPLICATE) UNITED STATES DEPARTMENT OF THE INTER GEOLOGICAL SURVEY | | Loss RIOR ^{Unit} | JAN 2 3 1961 | | |
|-------------|--|------------------|--------|--|-------------------------------------|------------------------------|--------------|--|--|
| N N N | NOTICE OF INTENTION TO DRILL | | | | SUBSEQUENT REPORT OF WATER SHUT-OFF | | | | |
| | (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) December 26, 1958 Bear Well No. 1 is located from ft. from $\begin{bmatrix} N \\ N \end{bmatrix}$ line and 30 ft. from $\begin{bmatrix} E \\ W \end{bmatrix}$ line of sec.19 | | | | | | | | |
| | włwł | 19 | 248 | 235 | 2.) X.) | .P.N. | - · · · J | | |
| | (1 / C) | c. and Sec. No.) | (Twp.) | (Rang | ge) | (Meridian) | | | |
| | (14 50) Malazza | | ¥2. | dav | | New Mer | Anor | | |

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-ing points, and all other important proposed work)

Verbal authority to plug and abandon was received by long distance telephone from Mr. Bob Evans on December 18, 1958. On December 19, 1958, a 15 sack cement plug was spotted from total depth to 2730. The 55" casing was pulled from 2400 and 20 sax of cement was spotted from 396" to 335". A 10 mack cement plug was placed in the top of surface pipe and the required marker erected. The location was classed up and the pits back filled on December 23, 1958.

| I understan | d that this plan of work must receive approval in writing | by the Geological Survey before operations may be commenced. |
|-------------|---|--|
| Company | SURBRINE POTALITY COMPANY | |
| | Box 5669 | |
| | Rosvell, New Mexico | By <u>2 Ala</u> |
| | | Title |
| | | Bine Durations |