	m 9 . Feb. 1	-331 8 951)	ι 	
İ				

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office LIFS Cruces
Lease No. Q49511
Unit

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLAN	SOUTH WEIGHT OF WATER SHUT-OFF
NOTICE OF INTENTION TO TEST WATER	The state of the s
NOTICE OF INTENTION TO RE-DRILL OR	
NOTICE OF INTENTION TO SHOOT OR AC	
NOTICE OF INTENTION TO PULL OR ALT	
NOTICE OF INTENTION TO ABANDON WE	ELL
(INDICATE	ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
(**************************************	TO THE DESCRIPTION OF REPORT, NOTICE, OR OTHER DATA)
	November 21 , 19 61
	1 646 G (N), 1 - 1 - 1 (F)
well ino is located	ft. from tine and the ft. from line of sec. 33
NW/4 of ME/4 Sec. 33 (½ Sec. and Sec. No.)	23S 31E N.M.P.H.
(% Sec. and Sec. No.)	(Twp.) (Range) (Meridian)
(Field)	(County or Subdivision) (State or Territory)
_	DETAILS OF WORK Dispective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)
The objective of this winch 20% surface casing circulated to the surface then will mud up with a will be run and comente pay zone. If well is p	pjective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points; and all other important proposed work) well is to test the Delaware sand at about 4400°. Seven will be set about 100° below ground level with cement ice. Water will be used as a drilling fluid to 4150° and salt base sud. If production is indicated 44° casing id, if necessary will acidize and fracture any prospective lugged as dry, cement plugs will be spotted in open hole
The objective of this winch 20% surface casing circulated to the surface then will mud up with a will be run and comente pay zone. If well is p	pjective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) well is to test the Delaware eard at about 4400°. Seven will be set about 300° below ground level with coment use. Water will be used as a drilling fluid to 4150° and salt base said. If production is indicated 44° casing id. If necessary will acidize and fracture any proposet in
The objective of this winch 20% surface casing circulated to the surface then will mud up with a will be run and comente pay zone. If well is p	pjective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) will be set about 100' below ground level with cement one. Water will be used as a drilling fluid to 4150' and salt base sud. If production is indicated 44' casing id, if necessary will acidize and fracture any prospective lugged as dry, cement plugs will be spotted in open hole or instructions of U.S. G. S. RECEIVED
The objective of this winch 20% surface casing circulated to the surface then will mud up with a will be run and cemented pay zone. If well is pland surface casing as posed	pjective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) well is to test the Delaware sand at about 4400°. Seven will be set about 100° below ground level with cement des. Water will be used as a drilling fluid to 4150° and salt base sud. If production is indicated 44° casing d. if necessary will acidize and fracture any prospective lugged as dry, cement plugs will be spotted in open hole for instructions of U.S. G. S. RECEIVED NOV 28 1961
The objective of this winch 20% surface casing circulated to the surface then will mud up with a will be run and cemented pay zone. If well is pland surface casing as posed	pjective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) will be set about 100' below ground level with cement one. Water will be used as a drilling fluid to 4150' and salt base sud. If production is indicated 4½' casing id, if necessary will acidize and fracture any prospective lugged as dry, cement plugs will be spotted in open hole or instructions of U.S. G. S. RECEIVED NOV 28 1961
The objective of this winch 20% surface casing circulated to the surface then will mud up with a will be run and cementer pay zone. If well is present and surface casing as perfect the s	pjective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) will be set about 100' below ground level with coment will be used as a drilling fluid to 4150' and salt base and. If production is indicated 44' casing id, if necessary will acidize and fracture any prospective lugged as dry, cement plugs will be spotted in open hole are instructions of U.S. G.S. RECEIVED NOV 28 1961 U.S. G. S. RECEIVED
The objective of this winch 20f surface casing circulated to the surface then will mud up with a will be run and comenter pay zone. If well is pland surface casing as perfectly and surface casing and surface cas	pjective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) will be set about 100' below ground level with coment will be used as a drilling fluid to 4150' and salt base and. If production is indicated 44' casing id, if necessary will acidize and fracture any prospective lugged as dry, cement plugs will be spotted in open hole are instructions of U.S. G.S. RECEIVED NOV 28 1961 U.S. G. S. RECEIVED
The objective of this winch 20% surface casing circulated to the surface then will mud up with a will be run and cementer pay zone. If well is possible and surface casing as possible the surface casing as possible to the surface casing as possi	pjective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) well is to test the Delaware sand at about 4400°. Seven will be set about 100° below ground level with coment will be used as a drilling fluid to 4130° and sait base and. If production is indicated 4½° casing id, if necessary will acidize and fracture any prospective lugged as dry, cement pluge will be spotted in open hole are instructions of U.S. G. S. RECEIVED NOV 28 1961 U.S. G. S. RECEIVED List receive approval in writing by the Geological Survey before operation flows and manufactured MEXICO ricks. Tional Bank Bldg.
The objective of this winch 20% surface casing circulated to the surface then will mud up with a will be run and cemented pay zone. If well is pland surface casing as possible that this plan of work much company PATOLL CORPORAL didress 605 Midland Material Corporations of the company of the corporation of the corpor	pjective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) will be set about 160° below ground level with cement will be used as a drilling fluid to 4150° and selt base and. If production is indicated 44° casing id, if necessary will acidize and fracture any prospective lugged as dry, cement plugs will be spotted in apen hole ar instructions of U.S. G. 3. RECEIVED NOV 28 1961 U.S. G. C.